Send Quote Requests to info@automatedpt.com
Call +1(800)985-6929 To Order or Order Online At Deltaacdrives.com



Digitized Automation for a Changing World

Delta Programmable Logic Controller DVP Series

reddot design award
winner 2010

www.deltaww.com

DELTA
Smarter. Greener. Together.


Send Quote Requests to info@automatedpt.com
Call +1(800)985-6929 To Order or Order Online At Deltaacdrives.com

The Perfect Small PLC Revolution!

After launching our first DVP series PLCs for industrial automation applications, Delta has been devoted to delivering more innovative products that satisfy customers' needs and meet the requirements of a wide variety of applications.

Delta PLCs offer a broad range of controllers and modules which all feature high performance, multiple functions and efficient program editing tools. In addition to the user-friendly programming software and faster execution speed, we provide complete industry-focused solutions, motion control solutions, and industrial fieldbus solutions with Delta's new PLC series. We also integrate our PLCs with industrial automation products to deliver total solutions for various field applications.

As your most reliable partner, Delta is dedicated to creating value for our customers.



Send Quote Requests to info@automatedpt.com
Call +1(800)985-6929 To Order or Order Online At Deltaacdrives.com



Contents

Page

Standard PLC DVP-E Series 5

Slim PLC DVP-S Series 10

General Motion Controller DVP-PM Series 12

Multi-axis Motion Controller DVP-MC Series 14

DVP Series Extension Modules 22

Electrical Specifications 27

Dimensions 28

PLC Editing Software ISPSoft 32

Touch / Text Panel HMI with Built-in PLC TP Series 34

DVP Series Model Name Instruction 38

DVP Series Function Overview 39

Ordering Information 40



Send Quote Requests to info@automatedpt.com
Call +1(800)985-6929 To Order or Order Online At Deltaacdrives.com

NEW

The 3rd Generation DVP-ES Series PLC gives you a better control experience with its NEW CPU



AS Core inside

Standard PLC

DVP-ES3

- Adopts the high performance processor (LD: 25 ns) of the Compact Modular Mid-range PLC AS Series
- Built-in 32/48/64/80 I/O points and supports high-speed counters / pulse-train outputs
- Built-in RS-485, Ethernet and CANopen
- Supports Modbus, Modbus TCP and EtherNet/IP
- Supports AS Series PLC instructions for higher scalability

Increased Built-in I/O Points to Enhance Competitiveness for Solutions

PLCs

DVP-28SS2
DVP-28SA2
DVP-26SE

- 16DI + 12DO (DVP-28SS2, DVP-28SA2)
- 14DI + 12DO (DVP-26SE)
- Compatible with DVP-S Series extension modules (right-side)



Complete Interface Design and 24-axis Motion Control



CANopen Motion Controller
DVP15MC

EtherCAT Motion Controller
DVP50MC

- 1GHz CPU
- Program capacity + data capacity = 20MB + 20MB
- Up to 24 real axes control

Built-in Interface

16DI 8DO	RS-232	RS485	Ethernet 15MC: x2 50MC: x1	Memory card:SD
CANopen DS301	Motion 15MC: CANopen DS402 50MC: EtherCAT	Incremental encoder interface*2	SSI absolute encoder interface	

Motion Function

Multi-axis Gear / Cam	Linear / Arc / Helical interpolation	Jerk	G-Code	Buffer Mode



reddot design award
winner 2010

Basic PLC

DVP-EC3

Applicable for sequence control and simple RS-485 / Modbus communication

- Built-in I/O: 10 / 14 / 16 / 20 / 24 / 30 / 32 / 40 / 48 / 60
- Program capacity: 4 k steps
- COM port: Built-in RS-232 & RS-485 ports (10 / 14-point models do not support RS-485), compatible with Modbus ASCII / RTU protocol
- Supports 2 points (Y0, Y1) of independent high-speed (max. 10 kHz) pulse output

  (Hardware version V8.00 and above support this function)

Built-in High-Speed Counters					
1-phase 1 input		1-phase 2 inputs		2-phase 2 inputs	
Counters	Bandwidth	Counters	Bandwidth	Counters	Bandwidth
2 / 2	20 kHz / 10 kHz	1	20 kHz	1	4 kHz

Standard PLC / Analog I/O PLC

DVP-ES2 / EX2

Standard PLCs with integrated communication and highly efficient processing ability for your control systems

- 32-bit CPU for high-speed processing
- Standard PLC DVP-ES2 Series: 16 / 20 / 24 / 32 / 40 / 60 / 80 I/O points for a variety of applications
- Analog I/O PLC DVP-EX2:
  - Built-in 12-bit 4 analog inputs / 2 analog output; and 14-bit analog I/O extension module
  - Built-in PID auto tuning function for a complete analog control solution
- Built-in 1 RS-232 and 2 RS-485 ports
- Program capacity: 16 k steps
- Data register: 10 k words
- Max. execution speed of basic instructions: 0.35 µs
- RTC function and file register (5 k words) (hardware version 2.0 and above)
- Highly efficient processing ability: 1 k steps of programs can be completed within 1ms
- Max. 100 kHz pulse control; specific motion control instructions (mark/masking and instant frequency changing) available for multi-axis applications
- Up to 4 levels of password protection secures your source programs and intellectual property

Built-in High-Speed Counters					
1-phase 1 input		1-phase 2 inputs		2-phase 2 inputs	
Counters	Bandwidth	Counters	Bandwidth	Counters	Bandwidth
2 / 6	100 kHz / 10 kHz	2	100 kHz	1 / 3	15 kHz / 5 kHz



Standard PLC with built-in CANopen interface

DVP32ES200RC / TC

Boosts productivity with high execution speed and built-in CANopen interface, and specializes in noise-immunity and easy wiring

- Built-in 1Mbps CANopen interface; COM3 supports standard CANopen DS301 protocol
- Versatile communication types: PDO, SDO, synchronous (SYNC), Emergency, NMT and many more
- 1Mbps high-speed transmission for large data:
  - Max. PDO transmission: up to 390 bytes
  - Max. PDO receiving: up to 390 bytes
- Ability to connect with 16 slaves via CANopen
- Built-in 1 RS-232 and 1 RS-485 ports

Standard PLC with built-in Ethernet interface

DVP-ES2-E

Higher communication speed and easier external connection with built-in Ethernet

- Built-in I/O: 20 / 32 / 40 / 60
- Communication speed: 100M
- Supports Modbus and EtherNet/IP (slave)
- Built-in 1 RS-232 and 2 RS-485 ports


Temperature / Analog I/O PLC

DVP30EX200R / T

Integrated controller for temperature control and analog input

- Built-in 16-bit 3 analog inputs / 12-bit 1 analog output
- Built-in PID auto tuning function to offer a complete analog control solution
- 3 analog inputs for Pt / Ni temperature input, precision of 0.1 degree can be readily achieved





Built-in Ethernet			
Modbus		**EtherNet/IP**	
Number of Connections	Server: 16 Client: 8	**Number of Connections**	TCP: 4 CIP: 8
Max. Data Exchange (each connection)	100 words	**Max. Data Exchange** (each connection)	250 words
		RPI	5~1,000 ms
		PPS	1,000 PPI

Built-in Analog I/O in DVP-EX2 Model			
Analog Input		**Analog Output**	
Channels	3	**Channels**	1
Resolution	16-bit	**Resolution**	12-bit
Spec.	-20~20 mA or -10~10 V	**Spec.**	0~20 mA or -10~10 V

Built-in Temperature Control Function		
Sensor	Pt100 / Pt1000	Ni100 / Ni1000
Temperature Range	-200 °C ~ 800 °C	-100 °C ~ 180 °C
Value Range	-2,000 ~ 8,000	-1,000 ~ 1,800

Send Quote Requests to info@automatedpt.com
Call +1(800)985-6929 To Order or Order Online At Deltaacdrives.com




Standard PLC


DVP-ES3 New

The 3rd Generation DVP-ES Series PLC provides higher performance with a new, upgraded CPU and multiple built-in communication interfaces


Program capacity



Data register



Execution speed



Outstanding Operation Performance

- Adopts the high performance processor of the Compact Modular Mid-range PLC AS Series
- Min. execution time of basic instruction: 25 ns

Excellent Motion Control

- High-speed counter: 200 kHz x 4
- High-speed pulse out: 200 kHz x 4 (pulse + direction) or 200 kHz x 4 (pulse)
- Supports 2-axis interpolation (linear and arc)
- Supports table structured position control function
- Supports 8 axes CANopen point-to-point motion control (with Delta servo drives only)

Built-in Communication Interfaces

- USB: For programming
- RS-485 x 2: Modbus RTU/ASCII
- Ethernet:
  - Modbus TCP: 16/16 connections (Server/Client)
  - EtherNet/IP: 8/16 connections (TCP/CIP)
- CANopen: DS301

Higher Specifications

- Program capacity: 64k steps
- Data capacity: 64k words
- Built-in 32/48/64/80 DIO points
- Supports micro SD card




High Performance PLC


DVP-EH3

High-end model of Delta's DVP-E Series PLC with large program capacity and data registers for demanding and complex applications


Program capacity



Data register



Execution speed



Excellent Motion Control

- High-speed pulse output: 4 axes of 200 kHz pulse output (DVP32/40/48/64/80EH00T3)
- Supports max. 4 hardware 200 kHz high-speed counters
- Various motion control instructions to achieve high-speed and high-precision positioning control for labeling machines, packaging machines, printing machines and more applications
- Linear / arc interpolation motion control function
- Provides up to 16 external interrupt pointers

Complete Program Protection

- Auto backup function prevents program and data loss even when the battery runs out
- Secondary backup function saves an extra copy of programs and data to enhance program safety
- Up to 4 levels of password protection protects your source programs and intellectual property

Outstanding Operation Performance

- 32-bit CPU + ASIC dual processors support floating point operations
- Max. execution speed of basic instructions: 0.24μs

Flexible Function Extension Modules & Cards

- Multiple selections of extension modules and function cards: analog I/O, temperature measurement, additional single-axis motion control, high-speed counting
- 3rd serial communication port and Ethernet communication card are available

PLC Link

- PLC Link allows users to link up a max. of 32 units to the network without extra communication extension modules

Built-in 4 Hardware High-Speed Counters

Standard		Hardware high-speed counter					
1-phase 1 input		1-phase 1 input		1-phase 2 inputs		2-phase 2 inputs	
Counters	Bandwidth	Counters	Bandwidth	Counters	Bandwidth	Counters	Bandwidth
8	10 kHz	4	200 kHz	4	200 kHz	4	200 kHz

The specifications of high-speed input and output on this page are applicable only for DVP40EH00R3 / DVP40EH00T3.


Refer to the I/O specifications table on page 20 for more information on other models.



High Performance Slim PLC

DVP-SV2

High-end model of the DVP-S Series with larger program capacities and data registers for more demanding and complex applications



Excellent Motion Control

- High-speed pulse output: 4 axes of 200 kHz pulse output
- Supports 4 hardware 200 kHz high speed counters
- Various motion control instructions to achieve high-speed and high-precision positioning control for labeling machines, packaging machines, printing machines and more applications
- Linear / arc interpolation motion control function
- Provides up to 16 external interrupt pointers

Complete Program Protection

- Auto backup function prevents program and data loss even when the battery runs out
- Secondary backup function saves an extra copy of programs and data to enhance program safety
- Up to 4 levels of password protection protects your source programs and intellectual property

Supports DVP-S Series modules (left-side and right-side); additional new Ethernet communication command (ETHRW)

Outstanding Operation Performance

- 32-bit CPU + ASIC dual processors support floating point operations
- Max. execution speed of basic instructions: 0.24μs

The DVP-24SV2 model has a built-in 2AI (12-bit) with Y10 / Y12 of 10 kHz output.

Built-in 4 Hardware High-Speed Counters							
Standard		Hardware high-speed counter					
1-phase 1 input		1-phase 1 input		1-phase 2 inputs		2-phase 2 inputs	
Counters	Bandwidth	Counters	Bandwidth	Counters	Bandwidth	Counters	Bandwidth
8	10 kHz	4	200 kHz	4	200 kHz4	4	200 kHz

The X11 / X15 have been upgraded to 200kHz since 2016 October

Send Quote Requests to info@automatedpt.com
Call +1(800)985-6929 To Order or Order Online At Deltaacdrives.com



Standard Slim PLC
DVP-SS2

Economic and compact model

- 32-bit CPU for high-speed processing
- Max. I/O: 480 points
- Program capacity: 8 k steps
- Data register: 5 k words
- Max. execution speed of basic instructions: 0.35 μs
- Built-in RS-232 and RS-485 ports (Master / Slave)
- Supports standard Modbus ASCII / RTU protocol and PLC Link function

Motion Control Functions

- 4 points of 10 kHz pulse output
- 8 points of high-speed counters: 20 kHz / 4 points, 10 kHz / 4 points

Advanced Slim PLC
DVP-SA2

Advanced model supporting 2-axis interpolation

- 32-bit CPU for high-speed processing
- Program capacity: 16 k steps
- Data register: 10 k words
- Max. execution speed of basic instructions: 0.35 μs
- Built-in 1 RS-232 and 2 RS-485 ports (Master / Slave)
  ※ Note: RS-485 will be reduced to 1 port in DVP28SA2
- Supports standard Modbus ASCII / RTU protocol and PLC Link function
- No battery required; RTC function operates for 15 days after power off
- Supports DVP-S Series modules (left-side and right-side)
  ※ Note: DVP28SA2 only supports right-side modules

Motion Control Functions

- 4 points of high-speed pulse output: 100 kHz / 2 points, 10 kHz / 2 points
- 8 points of high-speed pulse input: 100 kHz / 2 points, 10 kHz / 6 points, 1 set of A / B phase 50 kHz
- Supports 2-axis linear and arc interpolation

Built-in High-Speed Counters					
1-phase 1 input		1-phase 2 inputs		2-phase 2 inputs	
Counters	Bandwidth	Counters	Bandwidth	Counters	Bandwidth
4 / 4	20 kHz / 10 kHz	2	20 kHz	2 / 2	10 kHz / 5 kHz

Built-in High-Speed Counters					
1-phase 1 input		1-phase 2 inputs		2-phase 2 inputs	
Counters	Bandwidth	Counters	Bandwidth	Counters	Bandwidth
2 / 6	100 kHz / 10 kHz	2	100 kHz	1 / 3	50 kHz / 5 kHz



Analog I/O Slim PLC
DVP-SX2

Analog model with highly efficient PID control function

- 32-bit CPU for high-speed processing
- Program capacity: 16 k steps
- Data register: 10 k words
- Max. execution speed of basic instructions: 0.35 μs
- Built-in 4 analog inputs / 2 analog outputs
- Built-in mini USB, RS-232 and RS-485 ports (Master / Slave)
- Supports standard Modbus ASCII / RTU protocol and PLC Link function
- PID Auto Tuning function for highly efficient PID control
- No battery required; RTC function operates for at least one week after power off (hardware version 2.0 and above)
- Supports DVP-S Series modules (left-side and right-side)

Motion Control Functions

- 4 points of high-speed pulse output: 100 kHz / 2 points, 10 kHz / 2 points
- 8 points of high-speed pulse input: 100 kHz / 2 points, 10 kHz / 6 points
- Supports 2-axis linear and arc interpolation

Built-in Analog I/O			
Analog Input		**Analog Output**	
Channels	4	**Channels**	2
Resolution	12-bit	**Resolution**	12-bit
Spec.	-20 ~ 20 mA or -10 ~ 10 V or 4 ~ 20 mA	**Spec.**	0 ~ 20 mA or -10 V ~ 10 V or 4 ~ 20 mA

Network Type Advanced Slim PLC
DVP-SE

Complete network communication functions for advanced industrial applications

- 32-bit CPU for high-speed processing
- Program capacity: 16 k steps
- Data register: 12 k words
- Max. execution speed of basic instructions: 0.64 μs
- Built-in Ethernet
  DVP12SE : Modbus & Ethernet/IP (Explicit message)
  DVP26SE : Modbus & Ethernet/IP (Adapter mode, explicit message)
- Built-in mini USB port, RS-485 port*2 and Ethernet port that supports Modbus TCP and EtherNet/IP Slave (adapter)
  ※ Note: RS-485 will be reduced to 1 port in DVP26SE
- IP Filter functions as firewall for first line protection against malware and network threats
- Supports DVP-S Series modules (left-side and right-side)
  ※ Note: DVP26SE only supports right-side modules
- No battery required; RTC function operates for 15 days after power off

Motion Control Functions

- 4 points of high-speed pulse output: 100 kHz / 2 points, 10 kHz / 2 points
- 8 points of high-speed pulse input: 100 kHz / 2 points, 10 kHz / 6 points, 1 set of A / B phase 50 kHz
- Supports 2-axis linear and arc interpolation

Built-in High-Speed Counters					
1-phase 1 input		**1-phase 2 inputs**		**2-phase 2 inputs**	
Counters	**Bandwidth**	**Counters**	**Bandwidth**	**Counters**	**Bandwidth**
2 / 6	100 kHz / 10 kHz	2	100 kHz	1 / 3	50 kHz / 5 kHz

General Motion Controller

DVP-PM



Standard Motion Controller

DVP10PM00M

Standard motion controller for general applications

- Built-in 24 I/O points. Max. 256 I/O points
- Program capacity: 64 k steps
- Data register: 10 k words
- Execution speed LD: 0.13 μs, MOV: 2.1 μs
- Built-in RS-232 and RS-485 ports
- 2 / 3 / 4 / 5 / 6 axes linear interpolation motion control
- Highly accurate PWM 200 kHz output, resolution 0.3%
- 8 groups of high-speed captures (mark correction, frequency measurement), comparative output, Mark / Mask function (for bag making)
- Supports standard Modbus ASCII / RTU protocol

Motion Control Functions

- High-speed pulse output: built-in 6 sets of A / B phase pulse outputs
- 2 sets of 200 kHz output, 4 sets of 1 MHz output
- 6 sets of high-speed counters and hardware digital filter for counting
- Supports MPG inputs
- Single-axis motion control function (supports MPG, single-speed and two-speed positioning)
- Electronic gear function

Advanced Motion Controller

DVP20PM00D / M / DT

Excellent as motion controllers or extension modules and supports advanced motion control functions

- Built-in 16 I/O points. Max. 512 I/O points
- Program capacity: 64 k steps
- Data register: 10 k words
- Compatible with G-code / M-Code
- 3-axis linear / arc / helical interpolation
- Supports electronic cam (2,048 points) function for flying shear and rotary cut applications
- All models can be applied as motion controllers or extension modules
- Built-in RS-232 and RS-485 ports, and supports standard Modbus ASCII/RTU protocol

Motion Control Functions


- Built-in A / B phase differential signal outputs: 2 sets (DVP20PM00D) / 3 sets (DVP20PM00M)
  Max. differential output frequency: 500 kHz
- Supports MPG inputs
- Single-axis motion control function (supports MPG, single-speed and two-speed positioning)
- Electronic gear function

Function Cards for DVP-PM

Model Name	Specifications	Features
DVP-FPMC	Ethernet / CANopen communication card	1. Complies with CANopen CiA301 V4.0.2 protocol. 2. Provides high-speed program upload/download via Ethernet.


* DVP-PM also supports DVP-EH series function cards: DVP-F2AD, DVP-F2DA, DVP-F232S and DVP-F485S

General Motion Controller DVP-PM Series: Pulse-train communication



Programming Software for DVP-PM Series: PMSoft

The programming software for G-Code editing, motion path simulation, positioning route planning and electronic cam setup



Variable Declaration

Separate from the program. The corresponding physical I/O point of the variable is defined only after the program is compiled. Users do not need to modify the program.



Function Block


- A completed project can be divided into many function blocks.
- Every function block can be used repeatedly, and the import / export function makes the programming more convenient.

Comprehensive Monitoring

The "program monitoring" and "device monitoring" allow users to keep track of program operation.

Motion Network Function Block

PLCopen Function Block allows users to easily use motion control functions



Electronic Cam

Electronic cam editing

Send Quote Requests to info@automatedpt.com
Call +1(800)985-6929 To Order or Order Online At Deltaacdrives.com

Multi-axis Motion Controller

DVP-MC


16-axis Motion Controller

DVP10MC11T

Perfect controller to offer highly stable multi-axis motion control solutions through CANopen communication



- Built-in 12 I/O points
  (8 sets of high-speed inputs,
  4 sets of high-speed outputs)
- Up to 16 axes synchronous control through CANopen communication
- Synchronization time: 4 axes in 2ms / 8 axes in 4ms
- Built-in motion control instructions of electronic cam, flying shear, rotary cut for easy operation
- High precision control with interpolation function




System Control Architecture

Extensions (left-side)

- Supports DVP-S Series modules (left-side):
  - —CANopen master
  - —DeviceNet master
  - —PROFIBUS slave
  - —load cell modules

Accessories

Standard CANopen communication cables, terminal resistor and distribution box



Built-in Functions

- Built-in Ethernet, RS-232 and RS-485 communication ports
- Built-in CANopen and encorder interface

Extensions (right-side)

Supports DVP-S Series modules (right-side): digital, analog and temperature modules

Motion Control

- Speed, position, torque control
- Supports Electronic gear, E-Cam (2,048 points), flying shear and rotary cut applications
- Compatible with G-code, 3 axes arc / helical interpolation, 8 axes linear interpolation
- High speed position capture and error compensation

CANopen Accessories

Model Name	Specifications	Features
UC-CMCXXX-01A	CANopen sub-line	RJ45 connector for both ends
UC-DN01Z-01A/02A	CANopen main-line / sub-line	AWG18 / AWG24 CANopen cables for long distance communication via CANopen
TAP-CN01/02/03	Distribution box	Built-in terminal resistor 120 Ω
TAP-TR01	Terminal resistor	Terminal resistor 120 Ω

Multi-axis Motion Controller

DVP15MC / DVP50MC New

The DVP15MC / DVP50MC Series is a multi-axis motion controller designed for the CANopen / EtherCAT network architecture. It supports CANopen / EtherCAT with built-in motion control instructions (BufferMode and Jerk) for flexible configuration and fast project development. DVP15MC / DVP50MC controls up to 24 real axes via Motion port. It also supports single axis motion control instructions such as speed, position, torque, homing, position setup and multi-axis motion control instructions such as electronic gear, electronic cam (E-Cam), rotatory cut and G-code.

DVP15MC / DVP50MC features multiple built-in communication interfaces, and can be easily connected to other equipment without additional communication modules. It also provides high-speed and reliable motion control via CANopen / EtherCAT for printing, packaging, wire cutting, robots and other automation control industries.

Motion Control

- Up to 24 real axes control
  (virtual axis no.: 1 ~ 32, can't be repetitive with real axis no.)
- Built-in motion control instructions and easy to use
- Supports encoder axis and virtual axis
- Single axis motion control instructions: speed, torque, homing, and position setup
- Application instructions: electronic gear, E-Cam, and rotary cut
- G-code: 8 axes linear / arc / helical interpolation
- Coordinates motion control instructions

Performance

- 1 GHZ high-speed floating point operation
- High-precision computing: supports LREAL (Double-precision floating-point format)
- Synchronization time:
  - DVP15MC: 4 axes in 2ms, 8 axes in 4ms
  - DVP50MC: 32 axes in 1ms
- Program capacity: 20 MB
- Data capacity: 20 MB



External Interfaces

- 1 CANopen port as host or slave station
- 1 Motion port (DVP15MC: CANopen, DVP50MC: EtherCAT)
- 16 high-speed inputs / 8 high-speed outputs
- 2 incremental encoder interfaces
- 1 SSI absolute encoder interface
- Ethernet port: DVP15MC x2, DVP50MC x1
- 1 SD card slot
- 1 RS-232 port and 1 RS-485 port
- Extension:
  - Left-side: supports up to 8 DVP-S Series modules (AIO / PROFIBUS Slave)
  - Right-side: compatible with DVP-S Series modules (240 DI, 240 DO and 8 special modules)


Motion Network and Wiring

- DVP15MC
  - Motion network: CANopen
  - Communication speed: Max. 1Mbps
  - Distance: Max. 100m (at 500 kbps)
- DVP50MC
  - Motion network: EtherCAT
  - Communication speed: Max. 100Mbps
  - Distance: Max. 50m (Node-to-node)
- Simple wiring, plug-and-play

Send Quote Requests to info@automatedpt.com
Call +1(800)985-6929 To Order or Order Online At Deltaacdrives.com

DVP15MC / DVP50MC Interface

Multiple built-in communication interfaces allow easy connection to other equipment without additional communication modules.



Left-side extension

Supports DVP-S Series left-side modules (AIO / PROFIBUS Slave)



Right-side extension


Supports DVP-S Series right-side modules (240 I/O, 8 special modules)

Simple Wiring, Plug-and-Play Motion Control Network


The DVP15MC / DVP50MC features stable CANopen / EtherCAT communication, simple wiring, plug-and-play functions, and communicates with servo drives (axes) via CANopen / EtherCAT network. Delta provides communication cable, terminal resistor and distribution box.

*Please refer to "Accessories" for detailed information.

DVP15MC:



DVP50MC:



Compatible with Servo Drives via Motion Port

- Delta's AC Motor Drives ASDA-A2-XXXX*-M / ASDA-A2-XXXX*-MN models support CANopen communication, and they are the only models that can be connected to a DVP10MC11T for motion control networks.
- Delta's AC Motor Drives ASDA-A3-XXXX*-M / ASDA-A2-XXXX*-M / ASDA-B3-XXXX*-M models support CANopen communication, and they are the only models that can be connected to a DVP15MC CANopen (Motion) port for motion control networks.
- Delta's AC Motor Drives ASDA-A3-XXXX*-E / ASDA-A2-XXXX*-E / ASDA-B3-XXXX*-E models support EtherCAT communication, and they are the only models that can be connected to a DVP50MC EtherCAT (Motion) port for motion control networks.





The standard CANopen port of DVP15MC / DVP50MC can be connected to all equipment that supports CANopen networks. The ASDA-A3 / A2 / B3 Series models provide high positioning accuracy and low-speed operation stability.

* XXXX represents output power and input voltage.

System Structure


DVP15MC / DVP50MC provides multiple industrial networks. As in the structure shown below, DVP15MC / DVP50MC can be connected to a variety of industrial automation equipment via Ethernet (upper layer), EtherCAT, CANopen, DeviceNet, PROFIBUS DP (middle layer) and RS-485 (lower layer, support Modbus).




DVP50MC
HMI
PC
Ethernet
PROFIBUS DP
CANopen
PROFIBUS Device (Master)
EtherCAT
(Motion)
AC Motor Drive
AC Servo Drive
Temperature Controller
HMI
EtherCAT
(Motion)
RS-232
HMI
RS-485
Temperature Controller
AC Motor Drive
PLC
Encoder


Motion Control

Supports BufferMode and Jerk motion instructions:




Supports Jerk motion instruction:

Modifies the Jerk value to make the velocity curve smoother



Supports BufferMode motion instruction:

Enables smooth transition between 2 instructions




Send Quote Requests to info@automatedpt.com
Call +1(800)985-6929 To Order or Order Online At Deltaacdrives.com

CANopen Configuration Software: CANopen Builder

- Features network arrangement, motion control programming, G-code editor / graph preview and E-Cam curve planning

- Supports international standard function blocks for motion control, enhancing program editing efficiency

- **Network Arrangement**
  Network scanning for listing all the equipment
- **Motion Control**
  Supports international standard function blocks for motion control
- **G-code Editor and Preview**
  G-code editing and preview, direct DXF files import available



- **Program Editing**
  CFC, LD, ST, function blocks connection and syntax check
- **E-Cam Curve Planning**
  Allows users to plan E-Cam curves according to their needs for more complex control

Professional Motion Control Applications

Designed as the most outstanding and economical motion controller, the DVP-PM Series provides flying shear, rotary cut, electronic cam and many advanced functions to achieve highly precise motion control

Robot Arm

Electronic Cam (E-Cam) function enables the robot arm to perform multi-axis control. After the required positions are memorized in the PLC, users can enable the electronic cam function to create the E-Cam profile and conduct trajectory tracking and multi-axes motion control required in robot arm applications.



High-Speed Cutting Machine

Average PLC cutting motion is limited by operation speed, poor synchronization, large amounts of calculations and long CPU processing time, resulting in a disproportionate cutting result and affecting the quality of end products. The basic demands, however, can be fulfilled under low speed while rough surface and low quality appear under high speed. The electronic cam function offered by DVP-PM and DVP-MC is able to generate dynamic cam curves for rotary cutting to ensure precise cutting results.



Digital Board Cutting Machine

The DVP-PM Series' built-in flying shear function is able to complete synchronous conveyance and cutting speed, and ensures precise cutting results on conveyor belts.



CNC Lathe

The DVP-PM Series controls multi-axis motion. Two axes complete the motion by linear or arc interpolation, and the other two work independently, controlling the independent or synchronous ascending / descending of the vertical axis on two sides.



High Performance PLC DVP-EH Series and Extension Modules

Small PLC with Highest Operation Efficiency

DVP-EH3

- Max. 512 I/O points
- 200 kHz high-speed pulse output
- High-speed extension modules
- Linear / Arc interpolation
- L type, supports extension modules (left-side)



Function Cards

RS-232 / RS-422 / RS-485 Communication (COM3 Port, DVP-EH3 series PLC only)

DVP-F232



DVP-F485



Analog I/O

DVP-F2AD
DVP-F2DA



Ethernet Communication

DVP-FEN01 (DVP-EH3 only)



Accessories

Data Backup Card

DVP-512FM (DVP-EH3 only)




DVPPCC01
(for general applications)



Data Transmission Cable

UC-MS030-01A



Model Name	Specifications
DVP16EH00R3	2 counters of 200 kHz input
DVP16EH00T3	2 counters of 200 kHz input, 2 axes of 200 kHz output
DVP20EH00R3	2 counters of 200 kHz input, 1 counter of 20 kHz input
DVP20EH00T3	2 counters of 200 kHz input, 2 axes of 200 kHz output
DVP32EH00R3	4 counters of 200 kHz input
DVP32EH00T3*2	4 counters of 200 kHz input, 4 axes of 200 kHz output
DVP32EH00M3	4 counters of 200 kHz input (Differential: 2 sets), 2 axes of 200 kHz output (Differential: 2 axes)
DVP32EH00R3-L*1	4 counters of 200 kHz input
DVP32EH00T3-L*1 *2	4 counters of 200 kHz input, 4 axes of 200 kHz output
DVP40EH00R3	4 counters of 200 kHz input
DVP40EH00T3	4 counters of 200 kHz input, 4 axes of 200 kHz output
DVP48EH00R3	4 counters of 200 kHz input
DVP48EH00T3	4 counters of 200 kHz input, 4 axes of 200 kHz output
DVP64EH00R3	4 counters of 200 kHz input
DVP64EH00T3	4 counters of 200 kHz input, 4 axes of 200 kHz output
DVP80EH00R3	4 counters of 200 kHz input
DVP80EH00T3	4 counters of 200 kHz input, 4 axes of 200 kHz output

AC power supply Inputs Outputs Relay output Transistor output Differential output

*1 Supports high-speed extension (left-side).
*2 DVP32EH Series produced after 2014 support 4 axes of 200 kHz output

Digital I/O Modules

- **Input Point Extension**
  DVP08HM11N
  DVP16HM11N
  DVP32HM11N



- **Output Point Extension**
  DVP08HN11R/T
  DVP32HN00R/T



- **Input/Output Point Extension**
  DVP08HP11R/T
  DVP16HP11R/T
  DVP32HP00R/T
  DVP48HP00R/T



Analog I/O Modules

Analog Function Extension

- **Analog Input**
  - DVP04AD-H2
    V: 14-bit
    I: 13-bit
  - DVP04AD-H3
    V: 16-bit
    I: 16-bit



- **Analog Output**
  - DVP04DA-H2
    V: 12-bit
    I: 12-bit
  - DVP04DA-H3
    V: 16-bit
    I: 16-bit



- **Analog Input/Output**
  - DVP06XA-H2
    Input 4CH/Output 2CH
    V: 12-bit/V : 12-bit
    I: 11-bit/I : 12-bit
  - DVP06XA-H3
    V: 16-bit
    I: 16-bit



Temperature Measurement

- **Sensor: Pt100**
  - DVP04PT-H2



- **Sensor:**
  - DVP04TC-H2
    J, K, R, S, E, N, T thermocouple
    0~150mV
  - DVP08TC-H2
    J, K, R, S, E, N, T thermocouple
    ±150mV



- **DVP32EH00R3-L & DVP32EH00T3-L: compatible with DVP-SV Series' high-speed extension modules (left-side)**

Motion Control

- **Single-Axis Positioning**
  - DVP01PU-H2



- **High-Speed Counter**
  - DVP01HC-H2



Standard PLC DVP-ES3 / ES2 / EX2 Series and Extension Modules

The Most Profitable Solution for Sequential Control

DVP-ES3 / ES2

Model Name	Specifications
DVP16ES200R	8 / 8 / R
DVP16ES200T	8 / 8 / T
DVP20ES200RE	12 / 8 / R / E
DVP20ES200TE	12 / 8 / T / E
DVP24ES200R	16 / 8 / R
DVP24ES200T	16 / 8 / T
DVP32ES200R	16 / 16 / R
DVP32ES200T	16 / 16 / T
DVP32ES211T	DC / 16 / 16 / T
DVP32ES200RC	16 / 16 / R / C
DVP32ES200TC	16 / 16 / T / C
DVP32ES200RE	16 / 16 / R / E
DVP32ES200TE	16 / 16 / T / E
DVP40ES200R	24 / 16 / R
DVP40ES200T	24 / 16 / T
DVP40ES200RE	24 / 16 / R / E
DVP40ES200TE	24 / 16 / T / E
DVP60ES200R	36 / 24 / R
DVP60ES200T	36 / 24 / T
DVP60ES200RE	36 / 24 / R / E
DVP60ES200TE	36 / 24 / T / E
DVP80ES200R	40 / 40 / R
DVP80ES200T	40 / 40 / T
DVP32ES311T New	DC / 16 / 16 / T / C / E
DVP32ES300T New	16 / 16 / T / C / E
DVP32ES300R New	16 / 16 / R / C / E
DVP48ES300T New	24 / 24 / T / C / E
DVP48ES300R New	24 / 24 / R / C / E
DVP64ES300T New	32 / 32 / T / C / E
DVP64ES300R New	32 / 32 / R / C / E
DVP80ES300T New	40 / 40 / T / C / E
DVP80ES300R New	40 / 40 / R / C / E

AC power supply · Inputs · Transistor output · Ethernet
DC power supply · Outputs · Relay output · CANopen

DVP-EX2

Model Name	Specifications
DVP20EX200R	8 / 6 / R / 4AI/2AO
DVP20EX200T	8 / 6 / T / 4AI/2AO
DVP30EX200R	16 / 10 / R / 3AI/1AO
DVP30EX200T	16 / 10 / T / 3AI/1AO

AC power supply · Inputs · Transistor output
DC power supply · Outputs · Relay output

reddot design award winner 2010



Digital I/O Modules

- **Input Point Extension**
  DVP08XM211N
  DVP16XM211N
- **Output Point Extension**
  DVP08XN211R/T
  DVP16XN211R/T
  DVP24XN200R/T
- **Input/Output Point Extension**
  DVP08XP211R/T
  DVP16XP211R/T
  DVP24XP200R/T
  DVP32XP200R/T



Analog I/O Modules

- **Input Point Extension**
  DVP04AD-E2
- **Output Point Extension**
  DVP04DA-E2
  DVP02DA-E2
- **Input/Output Point Extension**
  DVP06XA-E2



Temperature Measurement Modules

DVP04PT-E2 · DVP06PT-E2 · DVP04TC-E2



DVP-ES2 Series Extension Cable Modules

DVPAEXT01-E2



Slim PLC DVP-S Series

Compact, Flexible Extension

DVP-SS2

Standard Slim PLC



Model Name	Specifications
DVP28SS211R	DC 16 12 R
DVP28SS211T	DC 16 12 T
DVP28SS211S New	DC 16 12 S
DVP14SS211R	DC 8 6 R
DVP14SS211T	DC 8 6 T
DVP12SS211S	DC 8 4 S

DC power supply Inputs Outputs
T Transistor output (NPN) R Relay output
S Transistor output (PNP)

DVP-SX2

Analog I/O Slim PLC



Model Name	Specifications
DVP20SX211R	DC 8 6 R 4AI/2AO
DVP20SX211T	DC 8 6 T 4AI/2AO
DVP20SX211S	DC 8 6 S 4AI/2AO

DC power supply Inputs Outputs
T Transistor output (NPN) R Relay output
S Transistor output (PNP)

DVP-SA2

Advanced Slim PLC



Model Name	Specifications
DVP28SA211R*1	DC 16 12 R
DVP28SA211T*1	DC 16 12 T
DVP28SA211S*1 New	DC 16 12 S
DVP12SA211R	DC 8 4 R
DVP12SA211T	DC 8 4 T

*1 The models do not support left-side modules.

DC power supply Inputs Outputs
T Transistor output (NPN) R Relay output

DVP-SV2

High Performance Slim PLC



Model Name	Specifications
DVP28SV11R2	DC 16 12 R
DVP28SV11T2	DC 16 12 T
DVP28SV11S2	DC 16 12 S
DVP24SV11T2	DC 10 12 T 2AI

DC power supply Inputs Outputs
T Transistor output (NPN) R Relay output
S Transistor output (PNP)

DVP-SE


Network Type Advanced Slim PLC



Model Name	Specifications
DVP26SE11R*1	DC 14 12 R
DVP26SE11T*1	DC 14 12 T
DVP26SE11S*1 New	DC 14 12 S
DVP12SE11R	DC 8 4 R
DVP12SE11T	DC 8 4 T

*1 The models do not support left-side modules.

DC power supply Inputs Outputs
T Transistor output (NPN) R Relay output



Slim PLC DVP-S Series
Extension Modules

High-speed Extension Modules (left-side)*1

Network Modules

- **DeviceNet Master**
  DVPDNET-SL
- **CANopen Master**
  DVPCOPM-SL



- **Ethernet**
  DVPEN01-SL
- **PROFIBUS-DP Slave**
  DVPPF02-SL



- **RS-422 / RS-485 Serial Communication Module**
  DVPSCM12-SL
- **BACnet MS / TP Slave Serial Communication Module**



Analog Extension

- **Analog Input**
  DVP04AD-SL
- **Analog Output**
  DVP04DA-SL



Load Cell / Tension

- **Load Cell Module**
  DVP01LC-SL
  DVP02LC-SL
  DVP201LC-SL
  DVP211LC-SL
  DVP202LC-SL



General Extension Modules (right-side)*2

I/O Point Extension

- **Input Point Extension**
  DVP08SM11N
  DVP16SM11N



- **Output Point Extension**
  DVP06SN11R
  DVP08SN11R / T
  DVP08SN11TS
  DVP16SN11T
  DVP16SN11TS



- **Input / Output Point Extension**
  DVP08SP11R / T
  DVP08SP11TS
  DVP16SP11R / T
  DVP16SP11TS



- **Pin Header Input**
  DVP32SM11N



- **Pin Header Output**
  DVP32SN11TN



- **Digital Switch**
  DVP08ST11N



Analog Extension

- **Analog Input**
  DVP04AD-S
  DVP06AD-S
  DVP04AD-S2



- **Analog Output**
  DVP04DA-S
  DVP02DA-S
  DVP04DA-S2



- **Analog Input / Output**
  DVP06XA-S
  DVP06XA-S2



Temperature Measurement

- **Sensor: Pt100, Pt1000**
  DVP04PT-S
  DVP06PT-S



- **Sensor: J,K,R,S,T thermocouple**
  DVP04TC-S



- **Sensor: New NTC thermistor**
  DVP08NTC-S



- **Temperature Control:**
  DVP02TUN-S
  DVP02TUR-S
  DVP02TUL-S



- **Remote Temperature Control Module:**
  DVP02TKN-S
  DVP02TKR-S
  DVP02TKL-S



Communication Modules

- **PROFIBUS Slave**
  DVPPF01-S



- **DeviceNet Slave**
  DVPDT01-S



Power Supply Modules

DVPPS01
DVPPS02
DVPPS05



Axis Control Module

- **Single-Axis Positioning**
  DVP01PU-S



*1. DVP32EH00R3-L & DVP32EH00T3-L are also compatible with the left-side high-speed extension modules.

*2. Max. quantity of right-side extension module is 14, among which the quantity of –S and –S2 modules must be equal to or less than 8. If the total quantity of extension modules is over 14, applying high density extension modules is recommended.

Specifications

Electrical Specifications

	AC	DC
Power Supply Voltage	100 ~ 240 V_{AC} (-15% ~ 10%), 50 / 60Hz ±5%	24 V_{DC} (-15% ~ 20%)
Fuse Capacity	2A / 250 V_{AC}	ES: 2A / 250 V_{AC}; SV: 2.5A / 30 V_{DC}
Spike Voltage Durability	1500 V_{AC} (Primary-secondary); 1500 V_{AC} (Primary-PE); 500 V_{AC} (Secondary-PE)	
Insulation Impedance	> 5 MΩ (all I/O point-to-ground: 500 V_{DC})	
Noise Immunity	ESD: 8 kV Air Discharge EFT: Power Line, 2 kV Digital I/O: 1 kV Analog & Communication I/O: 1 kV RS: 26 MHz ~ 1 GHz, 10 V/m	
Earth	The diameter of grounding wire shall not be shorter than that of the power supply cable. (When many PLCs are in use at the same time, please make sure every PLC is properly grounded.)	
Storage / Operation	Storage: -25 °C ~ 70 °C (temperature); 5% ~ 95% (humidity) Operation: 0 °C ~ 55 °C (temperature); 5% ~ 95% (humidity); pollution degree 2	
Conformal Coating	Yes	

Input Specifications*1

Max. Input Frequency		10 kHz	20 kHz	100 kHz	200 kHz
Input Signal Type		NPN (Sink) / PNP (Source)			
Input Signal Voltage		24 V_{DC} ±10% (5 mA)			
Response time*2	**DVP-EH3 / SV2 / PM**	OFF→ON: 20 µs ON→OFF: 50 µs	ES / EX / SX / SS2 / SX2 OFF→ON: 3.5 µs ON→OFF: 20 µs	ES2 / EX2 / SA2 / SX2 OFF ON: 2.5 µs ON→OFF: 5 µs	ES3 / EH3 / SV2 / PM OFF→ON: 0.15 µs ON→OFF: 3 µs
	DVP-ES3 / ES2 / EX2				
	DVP-ES / EX				
	DVP-SX				
	DVP-SS2				
	DVP-SA2 / SX2 / SE				

*1. For more detailed specifications, see the "Specification" section in the instruction sheet of each model.

*2. When the input point on PLC conducts only general input functions, use D1020 or D1021 to adjust the response time (default: 10ms).

Output Specifications*1

		Relay-R	Transistor-T		
			General-speed	High-speed	
Max. Exchange (working) Frequency		1Hz*2	10 kHz	100 kHz	200 kHz
Current spec.	**DVP-EH3 / SV2 / PM**	2A / 1 Point	0.3A / point @40 °C	SA2 / SX2 / ES2 / EX2 / SE Resistive: 0.5A / point (4A / COM) Conductive: 12 W (24 V_{DC}) Light bulb: 2 W (24 V_{DC})	ES3 / EH3 / SV2 / PM Resistive: 0.5A / point (4A / COM) Conductive: 12 W (24 V_{DC}) Light bulb: 2 W (24 V_{DC})
	DVP-ES3 / ES2 / EX2				
	DVP-ES / EX				
	DVP-SX	1.5A / 1 Point			
	DVP-SS2 / SA2 / SX2 / SE				
Voltage Spec.		250 V_{AC} / 30 V_{DC}	30 V_{DC}		
Response Time		10 ms	OFF→ON: 20 µs ON→OFF: 30 µs	OFF→ON: 2 µs ON→OFF: 3 µs	OFF→ON: 0.5 µs ON→OFF: 2.5 µs

*1. For more detailed specifications, see the "Specification" section in the instruction sheet of each model.


*2. Relay life: Resistive load more than 200,000 times; conductive load more than 80,000 times.

Send Quote Requests to info@automatedpt.com
Call +1(800)985-6929 To Order or Order Online At Deltaacdrives.com

Dimensions (unit: mm)


DVP-ES2/EX2 Series

Model Name (mm)	L	L1
DVP16ES200R/T	105	97
DVP20ES200RE	125	117
DVP20ES200TE	125	117
DVP24ES200R/T	125	117
DVP32ES200R/T	145	137
DVP32ES200RC	145	137
DVP32ES200TC	145	137
DVP32ES200RE	165	157
DVP32ES200TE	165	157
DVP32ES211T	145	137
DVP40ES200R/T	165	157
DVP40ES200RE	194	186
DVP40ES200TE	194	186
DVP60ES200R/T	225	217
DVP60ES200RE	255	247
DVP60ES200TE	255	247
DVP80ES200R/T	302	294
DVP20EX200R/T	145	137
DVP30EX200R/T	165	157




DVP-ES3 Series

Model Name (mm)	L	L1
DVP32ES300T/R New	165	157
DVP48ES300T/R New	216	208
DVP64ES300T/R New	267	259
DVP80ES300T/R New	310	302
DVP32ES311T New	165	157




DVP-PM Series

Model Name (mm)	H	H1	W	W1	W2
DVP20PM00D	90	80	174	164	82
DVP20PM00M	90	80	174	164	82
DVP10PM00M	90	80	143. 5	133. 5	82



DVP-ES3/ES2/EX2 Series


Model Name (mm)	L	L1	Type
DVP08XM211N	45	37	①
DVP08XP211R/T	45	37	①
DVP08XN211R/T	45	37	①
DVP16XM211N	70	62	②
DVP16XP211R/T	70	62	②
DVP16XN211R/T	70	62	②
DVP24XP200R/T	145	137	②
DVP24XN200R/T	145	137	②
DVP32XP200R/T	145	137	②
DVP04AD-E2	70	62	②
DVP02DA-E2	70	62	②
DVP04DA-E2	70	62	②
DVP06XA-E2	70	62	②
DVP04PT-E2	70	62	②
DVP06PT-E2 New	70	62	②
DVP04TC-E2	70	62	②



DVP-EH3 Series


Model Name (mm)	H	H1	W	W1	W2
DVP16EH00R3 / T3	90	80	113	103	82
DVP20EH00R3/T3	90	80	113	103	82
DVP32EH00M3	90	80	143.5	133.5	82
DVP32EH00R3/T3	90	80	143.5	133.5	82
DVP32EH00R3-L	90	80	143.5	133.5	82
DVP32EH00T3-L	90	80	143.5	133.5	82
DVP40EH00R3/T3	90	80	158.8	153.8	82
DVP48EH00R3/T3	90	80	174	164	82
DVP64EH00R3/T3	90	80	212	202	82
DVP80EH00R3/T3	90	80	276	266	82

*The dimensions of the DVP-EH3 and DVP-EH2 Series are the same.




DVP-SV / SX2 / MC Series

Model Name (mm)	H	H1	W	W1
DVP28SV11R2/T2	60	90	70	53.2
DVP20SX211R/T/S	60	90	70	53.2
DVP10MC11T	60	90	70	53.2




Model Name (mm)	H	H1	W	W1
DVP15MC11T New	110	116.2	128	68.4
DVP15MC11T-06 New	110	116.2	128	68.4
DVP50MC11T/P New	110	116.2	128	68.4
DVP50MC11T-04S/06/16S New	110	116.2	128	68.4



DVP-EH3 Series
I/O & Extension Modules


Model Name (mm)	H	H1	W	W1	W2
DVP08HM11N	90	80	40	36	82
DVP16HM11N	90	80	55	51	82
DVP32HM11N	90	80	143.5	133.5	82 .2
DVP08HN11R/T	90	80	40	36	82
DVP32HN00R/T	90	80	143.5	133.5	82 .2
DVP08HP11R/T	90	80	40	36	82
DVP16HP11R/T	90	80	55	51	82
DVP32HP00R/T	90	80	143.5	133.5	82 .2
DVP48HP00R/T	90	80	174	164	82 .2
Model Name (mm)	**H**	**H1**	**W**	**W1**	**W2**
DVP04AD-H2	90	80	60	56	82
DVP04DA-H2	90	80	60	56	82
DVP06XA-H2	90	80	60	56	82
DVP04PT-H2	90	80	60	56	82
DVP04TC-H2	90	80	60	56	82
DVP01PU-H2	90	80	60	56	82
DVPDT02-H2	90	80	40	46	82
DVPCP02-H2	90	80	40	46	82
DVPPF02-H2	90	80	40	46	82
DVP04AD-H3	90	80	60	56	82
DVP04DA-H3	90	80	60	56	82
DVP06XA-H3	90	80	60	56	82

*The dimensions of the DVP-EH3 and DVP-EH2 Series are the same.




DVP-SE / SX / SS2 / SA2 Series

Model Name (mm)	H	H1	W	W1
DVP28SS211R/T/S	96	90	46	60
DVP28SA211R/T/S	96	90	46	60
DVP26SE11R/T/S	96	90	46	60
DVP14SS211R/T	96	90	25.2	60
DVP12SS211S	96	90	25.2	60
DVP12SA211R/T	96	90	37.4	60
DVP12SE11R/T	96	90	37.4	60
DVP10SX11R/T	96	90	37.4	60




High-Speed Extension Modules (left-side)

Model Name (mm)	H	H1	W	W1
DVPEN01-SL	96	90	33.1	60
DVPCOPM-SL	96	90	33.1	60
DVPDNET-SL	96	90	33.1	60
DVPPF02-SL	96	90	33.1	60
DVPSCM12-SL	96	90	33.1	60
DVPSCM52-SL	96	90	33.1	60
DVP04AD-SL	96	90	33.1	60
DVP04DA-SL	96	90	33.1	60
DVP01LC-SL	96	90	33.1	60
DVP02LC-SL	96	90	33.1	60
DVP201LC-SL	96	90	33.1	60
DVP202LC-SL	96	90	33.1	60
DVP211LC-SL	96	90	33.1	60




Remote I/O Modules

Model Name (mm)	H	H1	W	W1
RTU-DNET	96	90	25.2	60
RTU-485	96	90	25.2	60
RTU-EN01	96	90	25.2	60
RTU-PD01	96	90	25.2	60
RTU-CN01 New	96	90	25.2	60
RTU-ECAT New	96	90	25.2	60




Remote Temperature Control Modules

Model Name (mm)	H	H1	W	W1
DVP02TKN-S	96	90	25.2	60
DVP02TKR-S	96	90	25.2	60
DVP02TKL-S	96	90	25.2	60




DVP-PS01 / 02 Power Supply Modules

Model Name (mm)	H	H1	W	W1
DVPPS01	100	90	36.5	60
DVPPS02	100	90	55	60




DVP-PS05 Power Supply Modules

Model Name (mm)	H	H1	W	W1
DVPPS05	93.3	90	60	63.4




PIN Definition of UC-MS030-01A




DVP-S Series I/O and Extension Modules

Model Name (mm)	H	H1	W	W1
DVP08SM11N	96	90	25.2	60
DVP16SM11N	96	90	25.2	60
DVP06SN11R	96	90	25.2	60
DVP08SN11R/T/TS	96	90	25.2	60
DVP08SP11R/T/TS	96	90	25.2	60
DVP16SP11R/T/TS	96	90	25.2	60
DVP16SN11T	96	90	25.2	60
DVP16SN11TS	96	90	25.2	60
DVP04AD-S	96	90	25.2	60
DVP04AD-S2	96	90	25.2	60
DVP06AD-S	96	90	25.2	60
DVP02DA-S	96	90	25.2	60
DVP04DA-S	96	90	25.2	60
DVP04DA-S2	96	90	25.2	60
DVP06XA-S	96	90	25.2	60
DVP06XA-S2	96	90	25.2	60
DVP04PT-S	96	90	25.2	60
DVP08NTC-S New	96	90	25.2	60
DVP06PT-S	96	90	25.2	60
DVP04TC-S	96	90	25.2	60
DVP01PU-S	96	90	25.2	60
DVPPF01-S	96	90	25.2	60
DVPDT01-S	96	90	25.2	60
DVP02TUN-S	96	90	25.2	60
DVP02TUR-S	96	90	25.2	60
DVP02TUL-S	96	90	25.2	60




Model Name (mm)	H	H1	W	W1
DVP32SN11TN	96	90	25.2	60
DVP32SM11N	96	90	25.2	60



PLC Editing Software: ISPSoft V2.0

Highly Accessible Programming Software with Fully Integrated Interface


Advanced Programming Interface + Visualized Hardware Configuration + Simplified Network Configuration




Advanced Programming Interface

Project Management Window

- **New functions:** Network configuration (NWCONFIG), hardware configuration (HWCONFIG) and PLC card utility
- 5 programming languages for programs and function blocks (FB): LD / FBD / SFC / IL / ST
- **Function Blocks:** Symbols can be introduced in call-by-value or call-by-reference types. Function blocks can be called in a function block for up to 32 levels
- **Monitor Table:** It can be stored and managed separately. Multiple monitor tables can be stored in a single project
- **User Library:** Users can design frequently used instructions for specific applications in different industries
- **Task:** Supports cyclic, I/O interrupt, timer interrupt, external interrupt, and more. Software will provide the usable tasks for different CPUs
- Built-in Delta Function Blocks provide a convenient programming environment for operators



Visualized Hardware Configuration



Module Selection

Module Description

Toolbar

- System hardware configuration can be monitored in On-Line mode
- Hardware configuration can be displayed by Scan function


Hardware Configuration Area


- Operations of Cut / Copy / Paste / Delete are available for modules and racks
- Parameters of each module can be directly configured

Rack Information

- I/O device range can be specified by the user

Simplified Network Configuration





Network Device Selection

Toolbar

Network Configuration Area

- Master device settings
- Ether Link editing function
- PLC Link editing function

Network Information

4-Line Text Panel HMI

TP04G-AL-C

TP04G-AL2

- ▶ 4.1" STN-LCD
- ▶ User-defined function keys available
- ▶ Supports RS-232/RS-422/RS-485 ports (TP04G-AL2)
- ▶ Password protection function available
- ▶ User-defined boot screen available
- ▶ Built-in real time clock (RTC)

Dimensions	4.1" (101.8 × 35.24 mm)
Resolution	192 × 64
Display Color	Monochrome
Flash Memory	256k bytes
Function Key	10 function keys
Password	Available
Recipe Function	Not available
RTC	Available
Serial COM Port	RS-232 & RS-422/485
Editing Software	TPEditor

4-Line Text Panel HMI

TP04G-BL-C

- ▶ 4.1" STN-LCD
- ▶ 0~9 numeric keys and user-defined function available
- ▶ Built-in RS-232 and RS-422/RS-485 ports
- ▶ Supports Modbus ASCII/RTU modes
- ▶ Password protection function available
- ▶ User-defined boot screen available
- ▶ Built-in real time clock (RTC)

Dimensions	4.1" (101.8 × 35.24 mm)
Resolution	192 × 64
Display Color	Monochrome
Flash Memory	256k bytes
Function Key	17 function keys
Password	Available
Recipe Function	Not available
RTC	Available
Serial COM Port	RS-232 & RS-422/485
Editing Software	TPEditor

8-Line Text Panel HMI

TP08G-BT2

- ▶ 3.8" STN-LCD
- ▶ Resolution: 240x128 dots
- ▶ Built-in 1,024KB flash memory
- ▶ 24 user-defined function keys
- ▶ Built-in RS-232 and RS-422/RS-485 ports
- ▶ Supports recipes and macro functions

Dimensions	3.8" (83x41 mm)
Resolution	240 × 128
Display Color	Monochrome
Flash Memory	1 M bytes
Function Key	24 function keys
Password	Available
Recipe Function	Available
RTC	Available
Serial COM Port	RS-232 & RS-422/485
Editing Software	TPEditor

Applications

Intelligent control systems for aquaculture, steel sleeve tapping machines, air compressors, plant factories

7-Inch Touch Panel HMI with Built-in PLC

TP70P-RM0

- ▶ Adopts the core of the DVP-SS2 Series PLC: program capacity: 2k steps / D device: 5k words
- ▶ 7" TFT-LCD
- ▶ Touch screen
- ▶ Built-in USB port for program upload / download
- ▶ Built-in RS-232 and RS-485 ports
- ▶ Supports Modbus ASCII / RTU modes
- ▶ Built-in real time clock (RTC)

Dimensions	7" (154 × 85 mm)
Resolution	800 × 480
Display Color	65,535 colors
Flash Memory	64 M bytes
Function Key	Not available
Password	Available
Recipe Function	Not available
RTC	Available
Serial COM Port	RS-232 & RS-485
Editing Software	TPEditor

7-Inch Touch Panel HMI with Built-in PLC

TP70P

- ▶ Adopts the core of the DVP-SS2 Series PLC: program capacity: 4 k steps / D device: 5k words
- ▶ Provides 2 sets of 10 kHz high-speed pulse input
- ▶ 7" TFT-LCD
- ▶ Touch screen
- ▶ Built-in USB port for program upload / download
- ▶ Built-in RS-485 port*2
- ▶ Supports Modbus ASCII / RTU modes
- ▶ Built-in real time clock (RTC)
- ▶ Digital and analog I/O terminals available


Dimensions	7" (154 × 85 mm)
Resolution	800 × 480
Display Color	65,535 colors
Flash Memory	64 M bytes
Function Key	Not available
Password	Available
Recipe Function	Not available
RTC	Available
Serial COM Port	2 sets of RS-485
Editing Software	TPEditor

4-Line Text Panel HMI with Built-in PLC

TP04P

- ▶ Adopts the core of the DVP-SS2 Series PLC: program capacity: 8 k steps / D device: 5k words
- ▶ Provides 2 sets of 10 kHz high-speed pulse input (Excludes TP04P-08TP1R)
- ▶ 4.1" STN-LCD
- ▶ Provides 0 ~ 9 numeric keys with user-defined function
- ▶ Built-in USB port for program upload/download
- ▶ Built-in RS-485 port*2
- ▶ Supports Modbus ASCII/RTU modes
- ▶ User-defined boot screen available
- ▶ Built-in real time clock (RTC)
- ▶ Digital and analog I/O terminals available


Dimensions	4.1" (101.8 × 35.24 mm)
Resolution	192 × 64
Display Color	Monochrome
Flash Memory	1 M bytes
Function Key	17 function keys
Password	Available
Recipe Function	Not available
RTC	Available
Serial COM Port	2 sets for RS-485
Editing Software	TPEditor

Model		Text Panel HMI						Text/Touch Panel HMI with Built-in PLC		
		TP02G-AS1	TP04G-AS2	TP08G-BT2	TP04G-AL-C	TP04G-AL2	TP04G-BL-C	TP04P-Series	TP04P-08TP1R	TP70P-Series
										
Display Specifications	Screen Type	STN-LCD								TFT-LCD
	Display Color	Monochrome								65,535
	Resolution	160 x 32	128 x 64	240 x 128	192 x 64					800 x 480
	Backlight	Life span of backlight is about 50,000 hours at 25°C								20,000 hours
	Display Range	72 x 22 mm	3" (67 x 32 mm)	3.8" (83 x 41 mm)	4.1" (101.8 x 35.24 mm)					7" (154 x 85 mm)
Flash Memory		256k bytes		1M bytes	256k bytes			1M bytes		64M bytes
Program Download Port		COM1 (RS-232)						COM1 (USB)		USB
Serial COM Port	COM1	RS-232	RS-232/422		RS-232	RS-232/422	RS-232	-		-
	COM2	RS-485			-	RS-422/485	RS-422/485	RS-485		**TP70 with I/O:** RS-485 **TP70R-RM0:** RS-232
	COM3	-			-	-	-	RS-485		
Extension Interface		The slot for program copy card								-
Real-time Clock		-	Built-in							
Auxiliary Keys	System Keys	6	7	12	5		7		5	-
	Function Keys	10	5	12	5		10		5	-
Operating Voltage		+24 V_{DC} (-10% ~ +20%)								-
Backup Battery		3V lithium battery CR2032 x 1/battery life: 5 years								
Buzzer		85 dB								
Cooling Method		Natural air circulation								
Operating Temperature		0 °C ~ 50 °C								
Storage Temperature		-20 °C ~ +60 °C								
Operating Humidity		10% ~ 90% RH (0 ~ 40°C)								
Vibration		IEC 61131-2, IEC 68-2-6 (TEST Fc); 5 Hz ≤ f < 8.4 Hz Continuous: 3.5 mm; 8.4 Hz ≦ f ≦ 150 Hz Continuous: 1.0 g								
Shock		IEC 61131-2, IEC 68-2-27 (TEST Ea); 15g peak, 11ms duration, half-sine, three shocks in each direction per axis, on 3 mutually perpendicular axes (total of 18 shocks)								
Radiated Emission		CISPR11, Class A Frequency: 30 ~ 230 MHz, Limits: 40 dB uV/m Frequency: 230 MHz ~ 1 GHz, Limits: 47 dB uV/m								
Radiated Electromagnetic Field		EN61000-4-3, Frequency: 80 ~ 2000 MHz, Limits: 10V/m								
Electrostatic Discharge		EN61000-4-2, Air Discharge: 8 KV, Contact Discharge: 4 KV								
Fast Transient Burst		EN61000-4-4, Power Line: 1 KV, Communication I/O: 500 V								
Dimensions Width (W) × Height (H) × Depth (D)		147 x 97 x 35.5		210 x 122 x 45	163.6 x 108.6 x 37		175.8 × 108.8 × 37	**TP04P Series:** 175.8 x 108.6 x 59.2 **TP04P-20EXL1T:** 175.8 x 108.6 x 82.4	175.8 x 108.6 x 37	**TP70P Series:** 205.6 x 142.6 x 49 **TP70P-RM0:** 205.6 x 142.6 x 37 **TP70P-211LC1T :** 205.6 x 142.6 x 87.7
Panel Cutout		136 x 85		196 x 108	151 x 96		163 × 96	163 × 96		191 × 128
Weight		240 g		430 g	268 g	270 g	292 g	**TP04PSeries:** 500 g **TP04P-20EXL1T:** 650 g	333 g	**TP70P Series:** 680 g **TP70P-RM0:** 620 g **TP70P-211LC1T:** 900 g
Safety Approvals (Waterproof Class of Front Panel)		IP66/NEMA4 & CE, UL Type 4 indoor			IP66/NEMA4 & CE, UL					
Editing Software		TPEditor V1								


Product Outline and Dimensions

Unit: mm

TP02G-AS1




TP04G-AS2




TP04G-AL-C/TP04G-AL2



TP04G-BL-C



TP04P-Series
(Exclude TP04P-08TP1R, TP04P-20EXL1T)



TP08G-BT2




TP70P-Series
(Exclude TP70P-RM0, TP70P-211LC1T)



TP70P-RM0




TP04P-08TP1R



TP04P-20EXL1T




TP70P-211LC1T



DVP Series Model Name Instructions

• PLC



1. Total I/O


2. Model
ES/ES2/ES3: DVP-ES/ES2/ES3 series PLC
EX/EX2: DVP-EX/EX2 series PLC
SS/SS2: DVP-SS/SS2 series PLC
SA/SA2: DVP-SA/SA2 series PLC
SX/SX2: DVP-SX/SX2 series PLC
SC: DVP-SC series PLC
SV: DVP-SV series PLC
SE: DVP-SE series PLC
PM: DVP-PM series PLC
MC: DVP-MC series PLC
EH: DVP-EH series PLC
EC: DVP-EC series PLC

3. Power supply
00: AC power input
11: DC power input

4. Output type
R: Relay
T: Transistor (NPN)
M: Mixed with differential signal
S: Transistor (PNP)
RC: Relay + CANopen
TC: Transistor + CANopen
RE: Relay + Ethernet
TE: Transistor + Ethernet

5. Version

• PI/PO Module




1. Total I/O

2. Module function
HC: High-speed counter
PU: Single-axis positioning module


3. Compatible model
S: DVP-SS/SA/SX/SC/SV/SS2/SA2
SX2/SV2/SE/MC Series PLC
H2/H3: DVP-EH2/EH3/PM Series PLC
SL: left-side extension for
DVP-S Series PLC

• Remote I/O



1. **Type**
DNET: DeviceNet
485: RS-485
EN01: Modbus TCP
CN01 : CANopen
ECAT : EtherCAT

• DI/DO Module



1. Total I/O


2. Model
X: DVP-ES/EX/ES2/EX2/ES3
series PLC
S: DVP-SS/SA/SX/SC/SV/SS2/
SA2/ SX2/SV2/SE/MC
series PLC
H: DVP-EH2/EH3/PM series PLC

3. I/O type
M: Input point
N: Output point
P: Input + output

4. Power supply
00: AC power input
11: DC power input

5. Output type
R: Relay
T: Transistor (NPN)
TS: Transistor (PNP
N: None output

• Function Card




1. Function Card

2. Function
232: RS-232 card
422: RS-422 card
485: RS-485 card
2AD: 2ch analog input
2DA: 2ch analog output

3. Particular definition
S: Slave mode
(applicable to COM3 coding only)

• Accessory: Cable




1. Accessory

2. Accessory definition
CAB: Cable

3. Type
1, 2, 3, 4, ...

4. Cable length
15: 1.5 m
30: 3.0 m

• AI/AO Module




1. Total I/O

2. Module function
AD: Analog/digital conversion
DA: Digital/analog conversion
PT: PT type temperature module
TC: Thermocouple type temperature
module
NTC : Thermistor type temperature
module
XA: AD+DA module
LC: Load cell module

3. Compatible model
S or S2: DVP-SS/SA/SX/SC/SV/SS2
SA2/SX2/SV2/SE/MC
Series PLC
SL: left-side extension for
DVP-S Series PLC
E2: DVP-ES2/EX2/ES3 Series PLC


• Network Module



1. Module function
EN01: Modbus TCP
DNET: DeviceNet master
COPM: CANopen master
CP02: CANopen Slave
DT01/02: DeviceNet Slave
PF01/02: PROFIBUS DP Slave

2. Compatible model
S: DVP-SS/SA/SX/SC/SV/SS2/
SA2/SX2/SV2/SE/MC Series PLC
H2/H3: DVP-
EH2/EH3/PM Series PLC
SL: left-side extension for
DVP-S Series PLC

• Accessory: Other



1. Accessory

2. Accessory definition
Bt: Battery

3. Type: 01, 02 .....

*For the availability of the product models, please contact Delta sales representatives or refer to "Ordering Information" in this catalogue.

DVP Series PLC Function Overview

Select your desired specifications and locate the most suitable PLC.

What do you need? → Select specifications → Check → Locate PLC

Item	Specifications	Check	Model							
			ES2	EX2	EH3	SS2	SA2	SX2	SV2	SE
Power Supply	AC	☐	◎	◎	○					
	DC	☐				○	○	○	○	○
I/O Points	< 256	☐	△	△						
	< 512	☐			△	△	△	△	△	△
Program Capacity	< 8 k	☐				○				
	<16 k	☐	○	○			○	○		○
	< 32 k	☐			○				○	
Output Type	Transistor (NPN)	☐	◎	◎	◎	◎	◎	◎	◎	◎
	Transistor (PNP)	☐				◎	△	◎	◎	△
	Relay	☐	◎	◎	◎	◎	◎	◎	◎	◎
	Differential signal	☐			◎					
Communication	3 COM ports (RS-232/485)	☐	○	○	△		○	△	△	△
	Ethernet	☐	◎		△		△	△	△	○
	USB	☐						○		○
	DeviceNet	☐			△*1		△*1	△*1	△*1	△*1
	CANopen	☐	◎		△*1		△*1	△*1	△*1	△*1
	PROFIBUS	☐			△*1		△*1	△*1	△*1	△*1
Positioning	2-axis output	☐	○	○	○	○	○	○		○
	4-axis output	☐			◎				○	
	> 4 axes	☐			△	△	△	△	△	△
	2-axis interpolation	☐	○	○	○		○	○	○	○
	100 kHz high speed	☐	○	○			○	○		○
	200 kHz high speed	☐			○	△	△	△	○	△
High-speed Counting	≤ 2 channels	☐	○	○		○	○	○		○
	≥ 3 channels	☐			○*3	△	△	△	○	△
	100 kHz high speed	☐	○	○			○	○		○
	200 kHz high speed	☐			○	△	△	△	○	△
Analog Function	< 4 channels (AD)	☐	△	○	△	△	△	○	△	△
	< 2 channels (DA)	☐	△	○*2	△	△	△	○*2	△	△

Note:

○ With such specification ◎ Varies upon model △ With such specification when connected to extension module / function card

*1: Series that support left-side modules can support both master and slave; other series support only slave

*2: DVP-EX / SX2 Series have 4 channels of analog input and 2 channels of analog output

*3: In addition to the built-in 4 channels of high-speed counters, the DVP-EH3 Series can connect high-speed counter modules

Ordering Information

DVP-EC3 Series PLC

Product Name	Power Supply	Output Method	Inputs	Outputs	Model Name	Certificates
DVP-EC3 Series Basic PLC	100~240 V_{AC}	Relay	6	4	DVP10EC00R3	CE cULus
	100~240 V_{AC}	Transistor	6	4	DVP10EC00T3	
	100~240 V_{AC}	Relay	8	6	DVP14EC00R3	
	100~240 V_{AC}	Transistor	8	6	DVP14EC00T3	
	100~240 V_{AC}	Relay	8	8	DVP16EC00R3	
	100~240 V_{AC}	Transistor	8	8	DVP16EC00T3	
	100~240 V_{AC}	Relay	12	8	DVP20EC00R3	
	100~240 V_{AC}	Transistor	12	8	DVP20EC00T3	
	100~240 V_{AC}	Relay	12	12	DVP24EC00R3	
	100~240 V_{AC}	Transistor	12	12	DVP24EC00T3	
	100~240 V_{AC}	Relay	18	12	DVP30EC00R3	
	100~240 V_{AC}	Transistor	18	12	DVP30EC00T3	

DVP-EC3 Series PLC

Product Name	Power Supply	Output Method	Inputs	Outputs	Model Name	Certificates
DVP-EC3 Series Basic PLC	100~240 V_{AC}	Relay	16	16	DVP32EC00R3	CE cULus
	100~240 V_{AC}	Transistor	16	16	DVP32EC00T3	
	100~240 V_{AC}	Relay	24	16	DVP40EC00R3	
	100~240 V_{AC}	Transistor	24	16	DVP40EC00T3	
	100~240 V_{AC}	Relay	28	20	DVP48EC00R3	
	100~240 V_{AC}	Transistor	28	20	DVP48EC00T3	
	100~240 V_{AC}	Relay	36	24	DVP60EC00R3	
	100~240 V_{AC}	Transistor	36	24	DVP60EC00T3	
Fastest execution time of basic instructions		3.8 μs	Execution time of MOV instruction		5.04 μs	

Ordering Information

DVP-ES3 / ES2 / EX2 Series PLC

Product Name	Power Supply	Output Method	Inputs	Outputs	Model Name	Certificates
DVP-ES3 Series New Standard PLC	24 V_{DC}	Transistor	16	16	DVP32ES311T	CE, cULus
	100 ~ 240 V_{AC}	Transistor	16	16	DVP32ES300T*2	
	100 ~ 240 V_{AC}	Relay	16	16	DVP32ES300R*2	
	100 ~ 240 V_{AC}	Transistor	24	24	DVP48ES300T*2	
	100 ~ 240 V_{AC}	Relay	24	24	DVP48ES300R*2	
	100 ~ 240 V_{AC}	Transistor	32	32	DVP64ES300T*2	
	100 ~ 240 V_{AC}	Relay	32	32	DVP64ES300R*2	
	100 ~ 240 V_{AC}	Transistor	40	40	DVP80ES300T*2	
	100 ~ 240 V_{AC}	Relay	40	40	DVP80ES300R*2	
DVP-ES2 Series Standard PLC	100 ~ 240 V_{AC}	Relay	8	8	DVP16ES200R	
	100 ~ 240 V_{AC}	Transistor	8	8	DVP16ES200T	
	100 ~ 240 V_{AC}	Relay	16	8	DVP24ES200R	
	100 ~ 240 V_{AC}	Transistor	16	8	DVP24ES200T	
	100 ~ 240 V_{AC}	Relay	16	16	DVP32ES200R	
	100 ~ 240 V_{AC}	Transistor	16	16	DVP32ES200T	
	24 V_{DC}	Transistor	16	16	DVP32ES211T	
	100 ~ 240 V_{AC}	Relay	24	16	DVP40ES200R DVP40ES200RM*1	
	100 ~ 240 V_{AC}	Transistor	24	16	DVP40ES200T	
	100 ~ 240 V_{AC}	Relay	36	24	DVP60ES200R	
	100 ~ 240 V_{AC}	Transistor	36	24	DVP60ES200T	
	100 ~ 240 V_{AC}	Relay	40	40	DVP80ES200R	
	100 ~ 240 V_{AC}	Transistor	40	40	DVP80ES200T	
DVP-ES2 Series Standard PLC with Built-in CANopen	100 ~ 240 V_{AC}	Relay	16	16	DVP32ES200RC	
	100 ~ 240 V_{AC}	Transistor	16	16	DVP32ES200TC	
DVP-ES2 Series Standard PLC with Ethernet Communication	100 ~ 240 V_{AC}	Relay	12	8	DVP20ES200RE	
	100 ~ 240 V_{AC}	Transistor	12	8	DVP20ES200TE	
	100 ~ 240 V_{AC}	Relay	16	16	DVP32ES200RE	
	100 ~ 240 V_{AC}	Transistor	16	16	DVP32ES200TE	
	100 ~ 240 V_{AC}	Relay	24	16	DVP40ES200RE	
	100 ~ 240 V_{AC}	Transistor	24	16	DVP40ES200TE	
	100 ~ 240 V_{AC}	Relay	36	24	DVP60ES200RE	
	100 ~ 240 V_{AC}	Transistor	36	24	DVP60ES200TE	
DVP-EX2 Series Analog PLC	100 ~ 240 V_{AC}	Relay	8	6	DVP20EX200R	
		Analog	4	2		
	100 ~ 240 V_{AC}	Transistor	8	6	DVP20EX200T	
		Analog	4	2		
DVP-EX2 Series Temperature / Analog PLC	100 ~ 240 V_{AC}	Relay	16	10	DVP30EX200R	
		Analog	3	1		
	100 ~ 240 V_{AC}	Transistor	16	10	DVP30EX200T	
		Analog	3	1		

Fastest execution time of basic instructions	ES3: 0.025μs ES2 / EX2: 0.35μs	Execution time of MOV instruction	ES3: 0.15μs ES2 / EX2: 3.4μs

*1: Built-in SD card slot
*2: Please contact our distributors for release date

DVP-ES3 / ES2 / EX2 Series Digital I/O Module (AC power supply)

Product Name	Power Supply	Output Method	Inputs	Outputs	Model Name	Certificates
Digital Module	100 ~ 240 V_{AC}	Relay	-	24	DVP24XN200R	CE, cULus
	100 ~ 240 V_{AC}	Transistor	-	24	DVP24XN200T	
	100 ~ 240 V_{AC}	Relay	16	8	DVP24XP200R	
	100 ~ 240 V_{AC}	Transistor	16	8	DVP24XP200T	
	100 ~ 240 V_{AC}	Relay	16	16	DVP32XP200R	
	100 ~ 240 V_{AC}	Transistor	16	16	DVP32XP200T	

DVP-ES3 / ES2 / EX2 Series Digital / Analog / Special Module ($24V_{DC}$)

Product Name	Output Method	Inputs	Outputs	Model Name	Certificates
Digital Module	-	8	-	DVP08XM211N	
	Relay	-	8	DVP08XN211R	
	Transistor	-	8	DVP08XN211T	
	Relay	4	4	DVP08XP211R	
	Transistor	4	4	DVP08XP211T	
	-	16	-	DVP16XM211N	
	Relay	-	16	DVP16XN211R	
	Transistor	-	16	DVP16XN211T	
	Relay	8	8	DVP16XP211R	
	Transistor	8	8	DVP16XP211T	
Analog I/O Module	• 4 points of analog voltage (10 V, 5 V) / current (20 mA, 0 ~ 20 mA, 4 ~ 20 mA) input *1 • Resolution: 14-bit (-32,000 ~ +32,000)			DVP04AD-E2	CE cULus
	• 4 points of analog voltage (-10 V ~ +10 V) / current (0 ~ 20 mA, 4 ~ 20 mA) output *1 • Resolution: 14-bit (-32,000 ~ +32,000) / (0 ~ +32,000)			DVP04DA-E2	
	• 2 points of analog voltage (-10 V ~ +10 V) / current (0 ~ 20 mA, 4 ~ 20 mA) output *1 • Resolution: 14-bit (-32,000 ~ +32,000) / (0 ~ +32,000)			DVP02DA-E2	
	• 4 points of analog voltage (10 V, 5 V) / current (20 mA, 0 ~ 20 mA, 4 ~ 20 mA) input *1 • Input resolution: 14-bit (-32,000 ~ +32,000) • 2 points of analog voltage (-10 V ~ +10 V) / current (0 ~ 20 mA, 4 ~ 20 mA) output • Output resolution: 14-bit (-32,000 ~ +32,000) / (0 ~ +32,000)			DVP06XA-E2	
Temperature Measurement Module	• 4 points of platinum RTD (Pt100, Pt1000, Ni100, Ni1000) sensor input / 0 ~ 300Ω resistance input *1 • Resolution: 16-bit • With PID temperature control			DVP04PT-E2	
	• 6 points of platinum RTD (Pt100, Pt1000, Ni100, Ni1000) sensor input / 0 ~ 300Ω resistance input *1 • Resolution: 16-bit • With PID temperature control			New DVP06PT-E2	
	• 4 points of thermocouple (J, K, R, S, T, E, N Type) sensor input / -80mV ~ +80mV voltage input *1 • Resolution: 20-bit • With PID temperature control			DVP04TC-E2	
Extension module	• Extends distance between the I/O modules of the DVP-ES2 Series within a given distance			DVPAEXT01-E2	

*1. Digital / analog photocoupler isolation. No isolation among channels.

DVP-EH3 Series PLC

Product name	Power Supply	Output Method	Inputs	Outputs	Model Name	Certificates
DVP-EH3 Series High Performance PLC	100 ~ 240V_{AC}	Relay	8	8	DVP16EH00R3	
	100 ~ 240V_{AC}	Transistor	8	8	DVP16EH00T3	
	100 ~ 240V_{AC}	Relay	12	8	DVP20EH00R3	
	100 ~ 240V_{AC}	Transistor	12	8	DVP20EH00T3	
	100 ~ 240V_{AC}	Transistor	16	16	DVP32EH00T3	
	100 ~ 240V_{AC}	Relay	16	16	DVP32EH00R3	
	100 ~ 240V_{AC}	Differential + Relay	16	16	DVP32EH00M3	CE cULus
	100 ~ 240V_{AC}	Relay	16	16	DVP32EH00R3-L	
	100 ~ 240V_{AC}	Transistor	16	16	DVP32EH00T3-L	
	100 ~ 240V_{AC}	Transistor	24	16	DVP40EH00T3	
	100 ~ 240V_{AC}	Relay	24	16	DVP40EH00R3	
	100 ~ 240V_{AC}	Relay	24	24	DVP48EH00R3	
	100 ~ 240V_{AC}	Transistor	24	24	DVP48EH00T3	
	100 ~ 240V_{AC}	Relay	32	32	DVP64EH00R3	
	100 ~ 240V_{AC}	Transistor	32	32	DVP64EH00T3	
	100 ~ 240V_{AC}	Relay	40	40	DVP80EH00R3	
	100 ~ 240V_{AC}	Transistor	40	40	DVP80EH00T3	
Execution time of basic instructions			0.24 μs			

Ordering Information

DVP-EH3 Series Digital / Analog Module

Product Name	Output Method	Inputs	Outputs	Model Name	Certificates
Digital Module	Relay	4	4	DVP08HP11R	
	Transistor	4	4	DVP08HP11T	
	Relay	-	8	DVP08HN11R	
	Transistor	-	8	DVP08HN11T	
	-	8	-	DVP08HM11N	
	Relay	8	8	DVP16HP11R	
	Transistor	8	8	DVP16HP11T	
	-	16	-	DVP16HM11N	
	-	32	-	DVP32HM11N	
	Relay	-	32	DVP32HN00R	
	Transistor	-	32	DVP32HN00T	
	Relay	16	16	DVP32HP00R	
	Transistor	16	16	DVP32HP00T	
	Relay	24	24	DVP48HP00R	
	Transistor	24	24	DVP48HP00T	
Analog Module	• 4 points of analog voltage (-10 V ~ +10 V) / current (-20 mA ~ +20 mA) *1 • Input resolution: 14-bit • Built-in RS-485 interface			DVP04 AD-H2	
	• 4 points of analog voltage (0 V ~ +10 V) / current (0 mA ~ +20 mA) output *1 • Resolution: 12-bit • Built-in RS-485 interface			DVP04DA-H2	CE
	• 4 points of analog voltage (-10 V ~ +10 V) / current (-20 mA ~ +20 mA) input • 2 points of analog voltage (0 V ~ +10 V) / current (0 mA ~ +20 mA) output • Resolution: 12-bit • Built-in RS-485 interface			DVP06XA-H2	c UL us
	• 4 points of platinum RTD (Pt100, Pt1000, Ni100, Ni1000) sensor input *1 / 0 ~ 300Ω or 0 ~ 3000Ω resistance input • Resolution: 0.1°C • Built-in RS-485 interface			DVP04PT-H2	
	• 4 points of thermocouple (J, K, R, S, T, E, N Type) sensor input *1 / 0 ~ 150mV voltage input • Resolution: 0.1°C • Built-in RS-485 interface			DVP04TC-H2	
	• 8 points of thermocouple (J, K, R, S, T, E, N Type) sensor input *1 / 0 ~ 150mV or ±150mV voltage input • Resolution: 0.1°C • Built-in RS-485 interface			DVP08TC-H2	
	• 4 channels of differential voltage (-10 V ~ +10 V) / current (-20 mA ~ +20 mA) input • Resolution: 16-bit • Built-in RS-485 interface			DVP04 AD-H3	
	• 4 channels of voltage (-10 V ~ +10 V) / current (0 ~ +20 mA) output • Resolution: 16-bit • Built-in RS-485 interface			DVP04DA-H3	
	• 4 channels of differential voltage (-10 V ~ +10 V) / current (-20 mA ~ +20 mA) input • 2 channels of voltage (-10 V ~ +10 V) / current (0 ~ +20 mA) output • Resolution: 16-bit • Built-in RS-485 interface			DVP06XA-H3	

*1. Digital / analog photocoupler isolation. No isolation among channels.

DVP-EH3 Series Extension Module / Function Card

Product Name	Description	Model Name	Certificates
Positioning Module	Servo position control module (single axis, 200 kHz)	DVP01PU-H2	
High-Speed Counter	High-speed counter module (1CH)	DVP01HC-H2	
Communication Module	PROFIBUS DP slave communication module	DVPPF02-H2	
	CANopen slave communication module	DVPCP02-H2	CE
	DeviceNet slave communication module	DVPDT02-H2	
Function Card	RS-232 port conversion (DVP-EH2: COM2; DVP-EH3: COM3)	DVP-F232	
	RS-485 port extension (COM3) (DVP-EH3 only)	DVP-F485	c UL us
	• 2 points of analog voltage (0 ~ 10 V) / current (0 ~ 20 mA) input • Resolution: 12-bit	DVP-F2AD	
	• 2 points of analog voltage (0 ~ 10 V) / current (0 ~ 20 mA) output • Resolution: 12-bit	DVP-F2DA	
	Ethernet communication card (compatible with controllers built-in with 32 I/O and above)	DVP-FEN01	

DVP-S Series PLC

Product Name	Power Supply	Output Method	Inputs	Outputs	Model Name	Certificates
DVP-SV2 Series Functional Slim PLC	24 VDC	Relay	16	12	DVP28SV11R2	CE cULus
	24 VDC	Transistor	16	12	DVP28SV11T2	
	24 VDC	Transistor (PNP)	16	12	DVP28SV11S2	
	24 VDC	Transistor	10 (2AI)	12	DVP24SV11T2	
Execution time of basic instructions			**0.24 µs**			
DVP-SS2 Series Standard Slim PLC	24 VDC	Relay	16	12	DVP28SS211R	CE cULus
	24 VDC	Transistor	16	12	DVP28SS211T	
	24 VDC	Transistor (PNP)	16	12	DVP28SS211S New	
	24 VDC	Relay	8	6	DVP14SS211R	
	24 VDC	Transistor	8	6	DVP14SS211T	
	24 VDC	Transistor (PNP)	8	4	DVP12SS211S	
DVP-SA2 Series Advanced Slim PLC	24 VDC	Relay	16	12	DVP28SA211R	
	24 VDC	Transistor	16	12	DVP28SA211T	
	24 VDC	Transistor (PNP)	16	12	DVP28SA211S New	
	24 VDC	Relay	8	4	DVP12SA211R	
	24 VDC	Transistor	8	4	DVP12SA211T	
DVP-SX2 Series Analog Slim PLC	24 VDC	Relay	8 (4AI)	6 (2AO)	DVP20SX211R	
	24 VDC	Transistor	8 (4AI)	6 (2AO)	DVP20SX211T	
	24 VDC	Transistor (PNP)	8 (4AI)	6 (2AO)	DVP20SX211S	
Fastest execution time of basic instructions		**0.35 µs**	**Execution time of MOV instruction**		**3.4 µs**	
DVP-SE Series Network Type Slim PLC	24 VDC	Relay	14	12	DVP26SE11R	CE cULus
	24 VDC	Transistor	14	12	DVP26SE11T	
	24 VDC	Transistor (PNP)	14	12	DVP26SE11S New	
	24 VDC	Relay	8	4	DVP12SE11R	
	24 VDC	Transistor	8	4	DVP12SE11T	
Fastest execution time of basic instructions		**0.64 µs**	**Execution time of MOV instruction**		**2 µs**	
DVP-SX Series Analog Slim PLC	24 VDC	Relay	4 (2AI)	2 (2AO)	DVP10SX11R	CE cULus
	24 VDC	Transistor	4 (2AI)	2 (2AO)	DVP10SX11T	
Fastest execution time of basic instructions		**3.8 µs**	**Execution time of MOV instruction**		**5.04 µs**	

DVP-S Series Digital / Analog Module

Product name	Output Method	Inputs	Outputs	Model Name	Certificates
Digital Module	Relay	-	6	DVP06SN11R	CE cULus
	Relay	-	8	DVP08SN11R	
	Transistor	-	8	DVP08SN11T	
	Transistor	-	16	DVP16SN11T	
	Relay	4	4	DVP08SP11R	
	Transistor	4	4	DVP08SP11T	
	-	8	-	DVP08SM11N	
	-	8	-	DVP08SM10N	
	Transistor (PNP)	-	8	DVP08SN11TS	
	Digital switch	8	-	DVP08ST11N	
	Relay	8	8	DVP16SP11R	
	Transistor (PNP)	4	4	DVP08SP11TS	
	Transistor (NPN)	8	8	DVP16SP11T	
	Transistor (PNP)	8	8	DVP16SP11TS	
	Transistor (PNP)	-	16	DVP16SN11TS	
	-	16	-	DVP16SM11N	
	Transistor, MIL	-	32	DVP32SN11TN	
	MIL	32	-	DVP32SM11N	
Product Name					
Analog I/O Module	▪ 4 points of analog input voltage (-10 V ~ +10 V) / current (-20 mA ~ +20 mA) ▪ Input resolution: 14-bit	▪ Built-in RS-485 interface ▪ Differential input		DVP04AD-S2	CE cULus
	▪ 4 points of analog output voltage (0 V ~ +10 V) / current (0 mA ~ +20 mA)	▪ Output resolution: 12-bit ▪ Built-in RS-485 interface		DVP04DA-S2	
	▪ Analog input+output module (6 points) ▪ 4 points of analog input voltage (-10 V ~ +10 V) / current (-20 mA ~ +20 mA) ▪ 2 points of analog output voltage (0 V ~ +10 V) / current (0 mA ~ +20 mA)	▪ Input / output resolution: 12-bit ▪ Built-in RS-485 interface ▪ Differential input		DVP06XA-S2	

Ordering Information

DVP-S Series Analog Module

Product Name	Description		Model Name	Certificates
Analog I/O Module	▪ 4 points of analog input voltage (-10 V ~ +10 V) / current (-20 mA ~ +20 mA) ▪ Input resolution: 14-bit	▪ Built-in RS-485 interface ▪ Single-ended input	DVP04AD-S	CE cULus
	▪ 4 points of analog output voltage (0 V ~ +10 V) / current (0 mA ~ +20 mA) ▪ Output resolution: 12-bit	▪ Built-in RS-485 interface	DVP04DA-S	
	▪ 2 points of analog output voltage (0 V ~ +10 V) / current (0 mA ~ +20 mA) ▪ Output resolution: 12-bit	▪ Built-in RS-485 interface	DVP02DA-S	
	▪ 6 points of analog input voltage (-10 V ~ +10 V) / current (-20 mA ~ +20 mA) ▪ Input resolution: 14-bit	▪ Built-in RS-485 interface	DVP06AD-S	
	▪ Analog input+output modules (6 points) ▪ 4 points of analog input voltage (-10 V ~ +10 V) / current (-20 mA ~ +20 mA) ▪ 2 points of analog output voltage (0 V ~ +10 V) / current (0 mA ~ +20 mA)	▪ Input / output resolution: 12-bit ▪ Built-in RS-485 interface ▪ Single-ended input	DVP06XA-S	

DVP-S Series Extension Module / High-Speed Module (Left-side)

Product Name	Description		Model Name	Certificates
High-Speed Analog I/O Module (Left-side)	▪ 4 groups of analog input *1 ▪ Signal range: 1 ~ 5 V, 0 ~ 5 V, -5 ~ 5 V, 0 ~ 10 V, -10 ~ 10 V, 4 ~ 20 mA, 0 ~ 20 mA, -20 ~ 20 mA ▪ Resolution: 16-bit ▪ Single channel On / Off setup enhances entire conversion efficiency ▪ Conversion time: 250 µs / point ▪ Off-line alarm (1 ~ 5 V, 4 ~ 20 mA)		DVP04AD-SL	CE cULus
	▪ 4 groups of analog output *1 ▪ Signal range: 0 ~ 10 V, -10 ~ 10 V, 4 ~ 20 mA, 0 ~ 20 mA ▪ Resolution: 16-bit ▪ Offers single channel On / Off setup ▪ Conversion time: 250 µs / point		DVP04DA-SL	
High-Speed Load Cell Module (Left-side)	▪ 1 set of load cell module *1 ▪ Resolution: 24-bit for hardware(ADC), 32-bit for data output	▪ Connectable to 4-wire / 6-wire load cell sensor ▪ Measurable range: 0 ~ 80 mV / V	DVP201LC-SL	
	▪ 1 set of load cell module *1 ▪ Resolution: 24-bit for hardware(ADC), 32-bit for data output ▪ Connectable to 4-wire / 6-wire load cell sensor	▪ Measurable range: 0 ~ 80 mV / V ▪ Built-in I/O control: 2DI / 4DO / 1AO	DVP211LC-SL	
	▪ 2 sets of load cell module *1 ▪ Resolution: 24-bit for hardware(ADC), 32-bit for data output	▪ Connectable to 4-wire / 6-wire load cell sensor ▪ Measurable range: 0 ~ 80 mV / V	DVP202LC-SL	
	▪ Supports 2 channels of load cell signal input *1 ▪ Resolution: 20-bit for hardware(ADC), 16-bit for data output ▪ Connectable to 4-wire / 6-wire load cell sensor ▪ Measurable range: 0 ~ 6 mV / V		DVP02LC-SL	
	▪ Supports 1 channel of load cell signal input *1 ▪ Resolution: 20-bit for hardware(ADC), 32-bit for data output ▪ Connectable to 4-wire / 6-wire load cell sensor ▪ Measurable range: 0 ~ 6 mV / V		DVP01LC-SL	
Temperature Measurement Module	▪ 6 points of platinum RTD (Pt100, Pt1000, Ni100, Ni1000) sensor input ▪ Resolution: 0.1 °C		DVP06PT-S	
	▪ 4 points of platinum RTD (Pt100, Pt1000, Ni100, Ni1000) sensor input *1 (Version 4.06 and above supports Pt1000, Ni100, Ni1000) ▪ Resolution: 0.1 °C ▪ Built-in RS-485 interface		DVP04PT-S	
	▪ 4 points of thermocouple (J, K, R, S, T type) sensor input *1 ▪ Resolution: 0.1 °C ▪ Built-in RS-485 interface		DVP04TC-S	
	▪ 8 points of thermistor (NTC) sensor input ▪ Resolution: 0.1 °C ▪ Built-in RS-485 interface		DVP08NTC-S New	
	▪ 2 points of universal analog input: 0 ~ 10 V, 0 ~ 20 mA, 4 ~ 20 mA; Thermocouple: J, K, R, S, T, E, N, B, C, L, U, TXK, PLII; RTD: Pt100, JPt100, Pt1000, Cu50, Cu100, Ni100, Ni1000, LG-Ni1000 ▪ Resolution: analog 16-bit; Sensor: 0.1 °C ▪ 4 points of NPN transistor output: 24 V_{DC} / 300mA ▪ Output point: built-in PID program control / manual control		DVP02TUN-S	

*1. Digital / analog photocoupler isolation. No isolation among channels.

DVP-S Series Extension Module / High-Speed Module (Left-side)

Product Name	Description	Model Name	Certificates
Temperature Measurement Module	▪ 2 points of universal analog input: 0 ~ 10 V, 0 ~ 20 mA, 4 ~ 20 mA; Thermocouple: J, K, R, S, T, E, N, B, C, L, U, TXK, PLII; RTD: Pt100, JPt100, Pt1000, Cu50, Cu100, Ni100, Ni1000, LG-Ni1000 ▪ Resolution: analog 16-bit; Sensor: 0.1 °C ▪ 4 points of relay output: 24V_{DC}/3 A ▪ Output point: built-in PID program control / manual control	DVP02TUR-S	CE cULus
	▪ 2 points of universal analog input: 0 ~ 10 V, 0 ~ 20 mA, 4 ~ 20 mA; Thermocouple: J, K, R, S, T, E, N, B, C, L, U, TXK, PLII; RTD: Pt100, JPt100, Pt1000, Cu50, Cu100, Ni100, Ni1000, LG-Ni1000 ▪ Resolution: analog 16-bit; Sensor: 0.1 °C ▪ 2 points of analog output: 0 ~ 10 V, 0 ~ 20 mA, 4 ~ 20 mA ▪ Output point: built-in PID program control / manual control	DVP02TUL-S	

*1. Digital / analog photocoupler isolation. No isolation among channels.

DVP-S Series Extension Module / High-Speed Module (Left-side)

Product Name	Description	Model Name	Certificates
Positioning Module	Servo position control module (single axis, 200 kHz)	DVP01PU-S	
Communication Module	DeviceNet slave communication module	DVPDT01-S	
	PROFIBUS DP slave communication module	DVPPF01-S	
Left-Side High-Speed Communication Module	Ethernet communication module, 10 / 100 Mbps	DVPEN01-SL	
	DeviceNet master communication module, 500 Kbps	DVPDNET-SL	
	CANopen master communication module, 1 Mbps	DVPCOPM-SL	
	PROFIBUS DP slave communication module , 12 Mbps	DVPPF02-SL	
	RS-485 / RS-422, serial communication module, 460 Kbps	DVPSCM12-SL	
	BACnet MS / TP Slave communication module, 460 Kbps	DVPSCM52-SL	
Remote I/O Module	RS-485 remote I/O module, connectable to DVP-S series I/O modules	RTU-485	
	Ethernet remote I/O module, connectable to DVP-S series I/O modules	RTU-EN01	
	DeviceNet remote I/O module, connectable to DVP-S series I/O modules	RTU-DNET	
	PROFIBUS remote I/O module, connectable to DVP-S series I/O modules	RTU-PD01	
	CANopen remote I/O module, connectable to DVP-S series I/O modules	RTU-CN01 New	
	EtherCAT remote I/O module, connectable to DVP-S series I/O modules	RTU-ECAT New	
Remote Temperature Control Module	▪ 2 points of universal analog input: 0 ~ 10 V, 0 ~ 20 mA, 4 ~ 20 mA; Thermocouple: J, K, R, S, T, E, N, B, C, L, U, TXK, PLII; RTD: Pt100, JPt100, Pt1000, Cu50, Cu100, Ni100, Ni1000, LG-Ni1000 ▪ Resolution: analog 16-bit; Sensor: 0.1 °C ▪ 4 points of NPN transistor output: 24V_{DC}/ 300mA ▪ Output point: built-in PID program control / manual control	DVP02TKN-S	
	▪ 2 points of universal analog input: 0 ~ 10 V, 0 ~ 20 mA, 4 ~ 20 mA; Thermocouple: J, K, R, S, T, E, N, B, C, L, U, TXK, PLII; RTD: Pt100, JPt100, Pt1000, Cu50, Cu100, Ni100, Ni1000, LG-Ni1000 ▪ Resolution: analog 16-bit; Sensor: 0.1 °C ▪ 4 points of relay output: 24V_{AC}/3 A ▪ Output point: built-in PID program control / manual control	DVP02TKR-S	
	▪ 2 points of universal analog input: 0 ~ 10 V, 0 ~ 20 mA, 4 ~ 20 mA; Thermocouple: J, K, R, S, T, E, N, B, C, L, U, TXK, PLII; RTD: Pt100, JPt100, Pt1000, Cu50, Cu100, Ni100, Ni1000, LG-Ni1000 ▪ Resolution: analog 16-bit; Sensor: 0.1 °C ▪ 2 points of analog output: 0 ~ 10 V, 0 ~ 20 mA, 4 ~ 20 mA ▪ Output point: built-in PID program control / manual control	DVP02TKL-S	

Communication Converter

Product Name	Description	Model Name	Certificates
Converter	USB to RS-485 converter	IFD6500	CE cULus
	USB to CAN converter	IFD6503	
	USB to RS-485 converter	IFD6530	
	EtherNet/IP, Modbus TCP to RS-232,RS-485 converter	IFD9506	
	DeviceNet to RS-232 / 485 converter	IFD9502	
	CANopen to RS-232 / 485 converter	IFD9503	
	RS-232 to RS-422 / 485 isolated converter	IFD8500-A	
	RS-485 to RS-422 isolated repeater	IFD8510-A	
	RS-422 / 485 to RS-232 addressable isolated converter	IFD8520	
	Bluetooth (BLE) to RS-485 converter	IFD8540 New	

Ordering Information

DVP-PM Series

Product Name	Power Supply	Output Method	Inputs	Outputs	Model Name	Certificates
Standard Motion Controller	100 ~ 240V$_{AC}$	Differential	16	16	DVP10PM00M	
		(Built-in 4-axis of independent 1MHz pulse output)				
Advanced Motion Controller	100 ~ 240V$_{AC}$	Differential	8	8	DVP20PM00DT	
		(Built-in 2-axis of independent 500 kHz pulse output)			DVP20PM00D	
		(Built-in 3-axis of independent 500 kHz pulse output)			DVP20PM00M	

Extension Module	Description	Model Name
DVP-PM communication card	Ethernet / CANopen communication card	DVP-FPMC

Execution time of basic instructions	0.13 µs	Execution time of MOV instruction	3.74 µs

DVP-MC Series

Product Name	Power Supply	Communication Protocol	Axes Controlled	Inputs	Outputs	Model Name	Certificates
Multi-axis Motion Controller	24 V$_{DC}$	CANopen DS402	16	8	4 (NPN)	DVP10MC11T	
			24	16	8 (NPN)	DVP15MC11T New	
			6	16	8 (NPN)	DVP15MC11T-06 New	
		EtherCAT	24	16	8 (NPN)	DVP50MC11T New	
			24	16	8 (PNP)	DVP50MC11P New	
			6	16	8 (NPN)	DVP50MC11T-06 New	
			4 (Point-to-Point)	16	8 (NPN)	DVP50MC11T-4S New	
			16 (Point-to-Point)	16	8 (NPN)	DVP50MC11T-16S New	

TP Series

Product Name	Description	Model	Certificates
TP02	Resolution: 160 x 32, Serial COM ports: RS-232 & RS-485	TP02G-AS1	
TP04	Resolution: 128 x 64, Serial COM ports: RS-232 & RS-422 / RS-485	TP04G-AS2	
	Resolution: 192 x 64, Serial COM ports: RS-232 & RS-422 / RS-485	TP04G-AL2	
	Resolution: 192 x 64, Serial COM ports: RS-232	TP04G-AL-C	
	Resolution: 192 x 64, Serial COM ports: RS-232 & RS-422 / RS-485, 0 ~ 9 numeric keys available	TP04G-BL-C	

Product Name	Description	DI	DO	AI*2	AO*2	PT	AX*1	LC	Output Type	Model	Certificates
TP04P	Resolution: 192 x 64 Serial COM ports: USB & RS-485*2	4 (60 Hz)	4						Relay	TP04P-08TP1R	
		8	8						Relay	TP04P-16TP1R	
		16	16						Relay	TP04P-32TP1R	
		8	8	4 (V/I)	2 (V/I)				Relay	TP04P-22XA1R	
		8	8	2 (I)	1 (I)	2			Relay	TP04P-21EX1R	
		8	8						Transistor	TP04P-16TP1T	
		16	16						Transistor	TP04P-32TP1T	
		8	8	4 (V/I)	2 (V/I)				Transistor	TP04P-22XA1T	
		8	8	2 (I)	1 (I)	2			Transistor	TP04P-21EX1T	
		9	16	4 (V/I)	2 (V/I) 4 (I)		2	1	Transistor	TP04P-20EXL1T*3	
TP70P	Resolution: 800 x 400 Serial COM ports: USB & RS-485*2	8	8						Relay	TP70P-16TP1R	
		16	16						Relay	TP70P-32TP1R	
		8	8	4 (V/I)	2 (V/I)				Relay	TP70P-22XA1R	
		8	8	2 (I)	1 (I)	2			Relay	TP70P-21EX1R	
		8	8						Transistor	TP70P-16TP1T	
		16	16						Transistor	TP70P-32TP1T	
		8	8	4 (V/I)	2 (V/I)				Transistor	TP70P-22XA1T	
		8	8	2 (I)	1 (I)	2			Transistor	TP70P-21EX1T	
		17	24		4 (I)		2	1	Transistor	TP70P-211LC1T*3	
TP08	Resolution: 240 x 128 / Serial COM ports: RS-232, RS-422 & RS-485 / 0~9 numeric numeric keypad									TP08G-BT2	

*1: Universal analog input (mA, V, RTD)
*2: V (Voltage), I (Current)
*3: USB & RS-485 are design with isolation

Software

Product Name	Description	OS (Windows-based Software)
ISPSoft	PLC editing software for AH, AS and DVP Series (supports 5 programming languages: LD, FBD, SFC, ST, IL)	Windows 2000, XP, Vista, Windows 7 (32-bit/64-bit)
WPLSoft	Programming software for DVP Series	Windows 98, Me, NT4.0, 2000, XP, Vista, Windows 7 (32-bit/64-bit)
TPEditor	Editing software for TP Series	Windows 98, Me, NT4.0, 2000, XP, Vista, Windows 7 (32-bit/64-bit)
PMSoft	Programming software for DVP-PM series	Windows 2000, XP, Vista, Windows 7 (32-bit/64-bit)
DCISoft	Delta communication integration software	Windows 2000, XP, Vista, Windows 7 (32-bit/64-bit)
DeviceNet Builder	DeviceNet configuration software	Windows 2000, XP, Vista, Windows 7 (32-bit/64-bit)
CANopen Builder	CANopen configuration software	Windows 2000, XP, Vista, Windows 7 (32-bit/64-bit)
NetView Builder	CAN bus message analysis software	Windows 2000, XP, Vista, Windows 7 (32-bit)

Starter Kit

Product Name	Model Name	Contents
Delta PLC Starter Kit	UT-14SS2-A	DVP14SS211R (PLC), DOP-107BV (HMI) and accessory
	UT-12SE-A1	DVP12SE11R (PLC), DOP-107EV (HMI) and accessory

Industrial Power Supply

Series	Power Supply	Inputs	Outputs	Power	Output Current	Model Name	Certificates
DVP	1-phase	85~264VAC	24VDC	24W	1A	DVPPS01	
				48W	2A	DVPPS02	
				120W	5A	DVPPS05	

*Note: For more ordering information, please refer to the catalogue for Delta Industrial Power Supply.

Accessories

Type	Model Name	Description	Specification		Applicable Modules
			Length	Connector / Terminal Block	
PLC Programming and Serial Communication Cable	UC-PRG015-01A	Communication cable for PLC (mini USB) to PC	1.5m	PC (USB←→mini USB) PLC	DVP-SE/DVP-SX2/AH500
	UC-PRG015-02A	Communication cable for TP (USB B type) to PC	1.5m	PC (USB←→USB B type) TP	TP70P/TP04P / DOP
	UC-PRG020-12A	Communication cable for PLC (DB9 female / 8-pin mini-DIN male) to PC	2m	PC (DB9 female←→8-pin mini-DIN male) PLC	DVP/TP RS-232
	UC-PRG030-01A	Communication cable for PLC (mini USB) to PC	3m	PC (USB←→mini USB) PLC	DVP-SE/SX2 AH500
	UC-PRG030-02A	Communication cable for TP (USB B type) to PC	3m	PC (USB←→USB B type) TP	TP70P / TP04P / DOP
	UC-PRG030-10A	Communication cable for PLC / HMI / TP (DB9 female) to PC	3m	PC (DB9 female←→DB9 female) PLC/HMI/TP	PLC/HMI/TP (DB9 female)
	UC-PRG030-20A	Communication cable for PLC / HMI (RJ45) to PC	3m	PC (RJ45←→RJ45) PLC/HMI	DVP-SE DVPEN02-L AHCPU5□□-EN AH10EN-5A
	UC-MS010-02A	Communication cable for PLC (8-pin mini-DIN male) to PC	1m	PC (DB9 female←→8-pin mini-DIN male) PLC	DVP PLC RS-232
	UC-MS020-01A	Communication cable for PLC (8-pin mini-DIN male) to PC	2m	PC (DB9 female←→8-pin mini-DIN male) PLC	
	UC-MS020-06A	Communication cable for PLC (8-pin mini-DIN male) to HMI	2m	HMI (DB9male←→8-pin mini-DIN male) PLC	
	UC-MS030-01A	Communication cable for PLC (8-pin mini-DIN male) to PC	3m	PC (DB9 female←→8-pin mini-DIN male) PLC	
	UC-MS030-06A	Communication cable for PLC (8-pin mini-DIN male) to HMI	3m	HMI (DB9male←→8-pin mini-DIN male) PLC	


Ordering Information

Accessories

Type	Model Name	Description	Specification		Applicable Modules
			Length	Connector / Terminal Block	
I/O External Terminal Module	UC-ET010-24A	I/O extension cable for connecting external terminal modules	1 m	PLC (MIL IDC40←→IDC40) external terminal modules	DVP32SM11N←→UB-10-ID32A DVP32SN11TN←→UB-10-OT32A
	UC-ET010-24B	I/O extension cable for connecting external terminal modules	1 m	PLC (MIL IDC40←→IDC40) external terminal modules (shielded wire)	DVP32SM11N←→UB-10-ID32A DVP32SN11TN←→UB-10-OT32A
	UC-ET010-24C	I/O extension cable for connecting external terminal modules	1 m	PLC (MIL IDC40←→IDC20x2) external terminal modules	DVP32SN11TN←→UB-10-OR16A
	UC-ET010-24D	I/O extension cable for connecting external terminal modules	1 m	PLC (MIL IDC40←→IDC20x2) external terminal modules (shielded wire)	DVP32SN11TN←→UB-10-OR16A
	UC-ET020-24B	I/O extension cable for connecting external terminal modules	2 m	PLC (MIL IDC40←→IDC40) external terminal modules (shielded wire)	DVP32SM11N←→UB-10-ID32A DVP32SN11TN←→UB-10-OT32A
	UC-ET020-24D	I/O extension cable for connecting external terminal modules	2 m	PLC (MIL IDC40←→IDC20x2) external terminal modules (shielded wire)	DVP32SN11TN←→UB-10-OR16A
	UC-ET030-24B	I/O extension cable for connecting external terminal modules	3 m	PLC (MIL IDC40 ←→ IDC40) external terminal modules (shielded wire)	DVP32SM11N←→UB-10-ID32A DVP32SN11TN←→UB-10-OT32A
	UC-ET030-24D	I/O extension cable for connecting external terminal modules	3 m	PLC (MIL IDC40 to IDC20x2) external terminal modules (shielded wire)	DVP32SN11TN←→UB-10-OR16A
Motion Control Cable / Industrial Communication Cable	UC-CMC003-01A	CANopen communication cable	0.3 m	RJ45	DVPCOPM-SL DVP10MC11T DVP15MC11T DVP15MC11T-06 DVPCP02-H2 TAP-CN03
	UC-CMC005-01A		0.5 m		
	UC-CMC010-01A		1 m		
	UC-CMC015-01A		1.5 m		
	UC-CMC020-01A		2 m		
	UC-CMC030-01A		3 m		
	UC-CMC050-01A		5 m		
	UC-CMC100-01A		10 m		
	UC-CMC200-01A		20 m		
	UC-EMC003-02A	EtherCAT communication cable (ETG approval)	0.3 m	RJ45	DVP50MC11T DVP50MC11T-06
	UC-EMC005-02A		0.5 m		
	UC-EMC010-02A		1 m		
	UC-EMC020-02A		2 m		
	UC-EMC050-02A		5 m		
	UC-EMC100-02A		10 m		
	UC-EMC200-02A		20 m		
	UC-EMC003-02B	EtherCAT communication cable	0.3 m	RJ45	
	UC-EMC005-02B		0.5 m		
	UC-EMC010-02B		1 m		
	UC-EMC020-02B		2 m		
	UC-EMC030-02B		3 m		
	UC-EMC050-02B		5 m		
	UC-EMC100-02B		10 m		
Industrial Communication Cable	UC-DN01Z-01A*1	DeviceNet / CANopen communication cable (Trunk cable - thick)	On customer's demand (up to 305 m)	--	DeviceNet / CANopen related models
	UC-DN01Z-02A*1	DeviceNet / CANopen communication cable (Drop cable - thin)		--	
External Terminal Module	UB-10-OR16A	external terminal module for DVP32SN output module	--	16-point relay output, 20-pin MIL	DVP32SN11TN
	UB-10-OT32A	external terminal module for DVP32SN output module	--	32-point transistor output, 40-pin MIL	DVP32SN11TN
	UB-10-ID32A	external terminal module for DVP32SM digital input module	--	32-point input, MIL	DVP32SM11TN
Connector	UN-03EN-04A	RJ45 connector	--	--	--
Peripheral Accessory	Data backup memory card (DVP-EH3 only)				DVP-512FM
	Data backup memory card (DVP-ES2 only)				DVP-E64FM
	Data backup memory card (64k words)				DVPPCC01
	Data backup memory card (TP only)				TP-PCC01
	Communication cable for PC (9-pin & 25-pin D-Sub) and PLC, 1.5 m				DVPACAB215
	Communication cable for PC (9-pin & 25-pin D-Sub) and PLC, 3 m				DVPACAB230
	4 types of RS-485 connectors				ADP485-01
	Connection cable for ADP485-01 and ASDA-A series servo				ADPCAB03A
	Connection cable for ADP485-01 and ASDA-B series servo				ADPCAB03B
	I/O extension cable for DVP-ES / EX Series, 0.3 m				DVPACAB403
	Extension cable for DVP-EH series PLC and extension module, 0.7 m				DVPACAB4A07
	DeviceNet / CANopen distribution box, 1 for 2				TAP-CN01
	DeviceNet / CANopen distribution box, 2 for 3				TAP-CN02
	DeviceNet / CANopen distribution box, 2 for 3 RJ45				TAP-CN03
	3.6 V lithium battery (unchargeable) for DVP-EH / SX Series PLC				DVPABT01
	Terminal resistance for CANopen communication (RJ45)				TAP-TR01
	Programming cable for TP Series				UCPRG030-10A

Note 1: Not available in Taiwan

Send Quote Requests to info@automatedpt.com
Call +1(800)985-6929 To Order or Order Online At Deltaacdrives.com



Send Quote Requests to info@automatedpt.com Call +1(800)985-6929 To Order or Order Online At Deltaacdrives.com

Smarter. Greener. Together.

Industrial Automation Headquarters

Taiwan: Delta Electronics, Inc.
Taoyuan Technology Center
No.18, Xinglong Rd., Taoyuan District,
Taoyuan City 33068, Taiwan
TEL: +886-3-362-6301 / FAX: +886-3-371-6301

Asia

China: Delta Electronics (Shanghai) Co., Ltd.
No.182 Minyu Rd., Pudong Shanghai, P.R.C.
Post code : 201209
TEL: +86-21-6872-3988 / FAX: +86-21-6872-3996
Customer Service: 400-820-9595

Japan: Delta Electronics (Japan), Inc.
Industrial Automation Sales Department
2-1-14 Shibadaimon, Minato-ku
Tokyo, Japan 105-0012
TEL: +81-3-5733-1155 / FAX: +81-3-5733-1255

Korea: Delta Electronics (Korea), Inc.
1511, 219, Gasan Digital 1-Ro., Geumcheon-gu,
Seoul, 08501 South Korea
TEL: +82-2-515-5305 / FAX: +82-2-515-5302

Singapore: Delta Energy Systems (Singapore) Pte Ltd.
4 Kaki Bukit Avenue 1, #05-04, Singapore 417939
TEL: +65-6747-5155 / FAX: +65-6744-9228

India: Delta Electronics (India) Pvt. Ltd.
Plot No.43, Sector 35, HSIIDC Gurgaon,
PIN 122001, Haryana, India
TEL: +91-124-4874900 / FAX: +91-124-4874945

Thailand: Delta Electronics (Thailand) PCL.
909 Soi 9, Moo 4, Bangpoo Industrial Estate (E.P.Z),
Pattana 1 Rd., T.Phraksa, A.Muang,
Samutprakarn 10280, Thailand
TEL: +66-2709-2800 / FAX: +66-2709-2827

Australia: Delta Electronics (Australia) Pty Ltd.
Unit 20-21/45 Normanby Rd., Notting Hill Vic 3168, Australia
TEL: +61-3-9543-3720

Americas

USA: Delta Electronics (Americas) Ltd.
5101 Davis Drive, Research Triangle Park, NC 27709, U.S.A.
TEL: +1-919-767-3813 / FAX: +1-919-767-3969

Brazil: Delta Electronics Brazil
Rua Itapeva, 26 - 3°, andar Edificio Itapeva,
One - Bela Vista 01332-000 - São Paulo - SP - Brazil
TEL: +55-12-3932-2300 / FAX: +55-12-3932-237

Mexico: Delta Electronics International Mexico S.A. de C.V.
Gustavo Baz No. 309 Edificio E PB 103
Colonia La Loma, CP 54060
Tlalnepantla, Estado de México
TEL: +52-55-3603-9200

EMEA

EMEA Headquarters: Delta Electronics (Netherlands) B.V.
Sales: Sales.IA.EMEA@deltaww.com
Marketing: Marketing.IA.EMEA@deltaww.com
Technical Support: iatechnicalsupport@deltaww.com
Customer Support: Customer-Support@deltaww.com
Service: Service.IA.emea@deltaww.com
TEL: +31(0)40 800 3900

BENELUX: Delta Electronics (Netherlands) B.V.
Automotive Campus 260, 5708 JZ Helmond, The Netherlands
Mail: Sales.IA.Benelux@deltaww.com
TEL: +31(0)40 800 3900

DACH: Delta Electronics (Netherlands) B.V.
Coesterweg 45, D-59494 Soest, Germany
Mail: Sales.IA.DACH@deltaww.com
TEL: +49(0)2921 987 0

France: Delta Electronics (France) S.A.
ZI du bois Challand 2, 15 rue des Pyrénées,
Lisses, 91090 Evry Cedex, France
Mail: Sales.IA.FR@deltaww.com
TEL: +33(0)1 69 77 82 60

Iberia: Delta Electronics Solutions (Spain) S.L.U
Ctra. De Villaverde a Vallecas, 265 1º Dcha Ed.
Hormigueras – P.I. de Vallecas 28031 Madrid
TEL: +34(0)91 223 74 20

Carrer Llacuna 166, 08018 Barcelona, Spain
Mail: Sales.IA.Iberia@deltaww.com

Italy: Delta Electronics (Italy) S.r.l.
Via Meda 2–22060 Novedrate(CO)
Piazza Grazioli 18 00186 Roma Italy
Mail: Sales.IA.Italy@deltaww.com
TEL: +39 039 8900365

Russia: Delta Energy System LLC
Vereyskaya Plaza II, office 112 Vereyskaya str.
17 121357 Moscow Russia
Mail: Sales.IA.RU@deltaww.com
TEL: +7 495 644 3240

Turkey: Delta Greentech Elektronik San. Ltd. Sti. (Turkey)
Şerifali Mah. Hendem Cad. Kule Sok. No:16-A
34775 Ümraniye – İstanbul
Mail: Sales.IA.Turkey@deltaww.com
TEL: + 90 216 499 9910

MEA: Eltek Dubai (Eltek MEA DMCC)
OFFICE 2504, 25th Floor, Saba Tower 1,
Jumeirah Lakes Towers, Dubai, UAE
Mail: Sales.IA.MEA@deltaww.com
TEL: +971(0)4 2690148

*We reserve the right to change the information in this catalogue without prior notice.

DELTA_IA-PLC_DVP-TP_C_EN_20210916

Send Quote Requests to info@automatedpt.com
Call +1(800)985-6929 To Order or Order Online At Deltaacdrives.com